

TYPICAL SECTION THRU EXISTING DECK

✱ Match existing concrete color. Apply tinted sealer to blend existing and new concrete repairs to existing concrete.

STANDARD DRAWING GUIDANCE (do not show on plans) :

This is an index of Standard Drawing details. Modify as required.

Transverse repair zoning over intermediate bents is required for these structures. Longitudinal repair zoning in spans is required only when hydro demolition is required and is based on anticipated quantity of deck repair if not overlayed, confidence of anticipated quantity of deck repair if overlayed, deck rating (e.g. 6 or better may not need zoning). See EPG 751.40 (if only transverse zoning is required. Zones shall be called "Special Repair Zones").

Wearing surface thickness can vary according to grade elevation requirements and minimum barrier curb height requirements. Max. thickness should be limited to 3" (Ref. Organizational Results Research Report OR06.004, May 2006).

(A) - Match or show difference as plus/minus x" (e.g. ± 2¼").
See Bridge Memorandum or SPM.

(B) - Identify new wearing surface and thickness. See Bridge Memorandum or SPM.

(C) - Identify existing wearing surface and thickness. See Bridge Memorandum or existing plans.

(D) - 1/4" typical. See Bridge Memorandun or SPM.

(E) - 1/2" min. See Bridge Memorandum for the minimum depth of total surface hydro demolition.

(F) - See existing plans.

(G) - Use appropriate reference line, ie. ℄ Structure, ℄ Roadway, ℄ Median, etc.

(H) - When detailing Epoxy Polymer Concrete Overlay, it is a preferred detailing practice to show a discernable overlay thickness on the plans.

(I) - Partial Depth Repair should only be allowed where anticipated quantity of deck repair is not significant and longitudinal zoning is not required.

(J) - Low Slump Concrete and Polyester Polymer Concrete are not allowed for Partial Depth Repair because they are too stiff to be poured monolithically and should only be used with Half-Soled Repair. Any other concrete wearing surface may be used for Partial Depth Repair.

(K) - Slab Edge Repair may be used in place of Superstructure Repair (Unformed) in these locations. (See Sec 704)

BOX BEAM WITHOUT EXISTING WEARING SURFACE



BOX BEAM WITH EXISTING WEARING SURFACE



BOX BEAM WITHOUT EXISTING WEARING SURFACE-HYDRO DEMOLITION



BOX BEAM WITH EXISTING WEARING SURFACE-HYDRO DEMOLITION



USE FOR ALL APPLICATIONS



RHB03.DgnBeam Effective: June 2015 Supersedes: Oct. 2012