

## ADDENDUM 005 Request for Bid Fulton Wash Bay Enclosure Project RFB 9-161115KH1

Bidders should acknowledge receipt of Addendum 005 (FIVE) by signing and including it with the original bid. The due date for receipt of bids **has** changed by this Addendum; the due date is **November 18, 2016 2:00 PM Central Time**. Accordingly, the following clarifications, and or additional information, are believed to be of general interest to all potential bidders. All other terms and conditions remain unchanged and in full force.

Name and Title of Signer (Print or type)	Name and Title of Department Authority  Kristi Hixson General Services Senior Specialist
Contractor/Offeror Signature  <hr/> (Signature of person authorized to sign)	Department of Transportation  <i>Kristi Hixson</i> <hr/> (Authorizing Signature)
Date Signed:	Date Signed: 11/15/2016

**As included in Addendum 001:**

Electrical Panel: Prior to contractor beginning work, MoDOT will upgrade current 50 amp electrical panel box to a size capable of servicing all electrical component tied into the wash bay enclosure project.

**Additional Electrical Clarification:**

MoDOT is only providing new panel box, all other electrical to be provided by contractor in base bid.

Replace Specification 09971 Fiberglass Wall Panels to the Fulton Wash Bay Enclosure Project Specifications included in Addendum 002 with the attached updated specification.



**FIBERGLASS WALL PANELS**

**PART 1 GENERAL**

1.1 SUMMARY

- A. Provide fiberglass wall panels where shown on the Drawings, as specified herein and as needed for a complete and proper installation.
- B. Related work:
  - 1. Documents affecting work of this Section include, but are not necessarily limited to, General Conditions, supplementary Conditions and Sections in division 1 of these Specifications.

1.2 SUBMITTAL

- A. Comply with pertinent provisions of Section 01300.
- B. Product data: Within 45 calendar days after the Contractor has received the Owner's Notice to Proceed, submit:
  - 1. Materials list of items proposed to be provided under this Section;
  - 2. Manufacturer's specifications and other data needed to prove compliance with the specified requirements;
  - 3. Manufacturer's recommended installation procedures which, when approved by the Architect, will become the basis for accepting or rejecting actual installation procedures used on the Work.

1.3 QUALITY ASSURANCE

- A. Use adequate numbers of skilled workmen who are thoroughly trained and experienced in the necessary crafts and who are completely familiar with the specified requirements and the methods needed for proper performance of the work of this Section.

1.4 DELIVERY, STORAGE AND HANDLING

- A. Comply with pertinent provisions of Section 01600.

**PART 2 PRODUCTS**

2.1 WALL PANELS

- A. Acceptable products:
  - 1. Nudo Products, Inc. distributed from 1500 Taylor Ave., Springfield, IL. 62703 1-800-826-4132. Fax 217-528-8722.
  - 2. Fiber-Corr, 7/16" pvc panel #F3C400-10. Color: White. Size: 4' x 10'. Surface: Textured.
  - 3. Equal products of other manufacturers approved in advance by the Architect.

2.2 OTHER MATERIALS

- A. Provide General Electric "Silicone Sealant SE 1200."
- B. Provide continuous vinyl division, inside and outside corner trim(s) by same manufacturer where required.
- C. Provide white low profile pancake head Quadrex Drive screws with spacing as recommended by the panel manufacturer.
- D. Provide other materials, not specifically described but required for a complete and proper installation, as selected by the Contractor subject to the approval of the Architect.

**PART 3 EXECUTION**

**3.1 SURFACE CONDITIONS**

- A. Examine the areas and conditions under which work of this Section will be performed. Correct conditions detrimental to timely and proper completion of the Work. Do not proceed until unsatisfactory conditions are corrected.

**3.2 INSTALLATION**

- A. Securely install the approved products in accordance with the manufacturer's recommendations as approved by the Architect, setting panels straight, plumb, level and true to the lines and levels shown on the Drawings, attached to the walls with the specified nails at 6" centers both ways.
- B. Finish butt joints, wall juncture, wall/ceiling and wall/curb joints with the specified sealant, tooling to a smooth finish.

**END OF SECTION**