

11' Replacement Flatbed Body

Minimum Requirements

General:

- Replacement 11'x102" flatbed body with 3/16" tread plate steel reinforced floor.
- Should include headache rack to prevent truck cab damage. Be suitable to mount existing warning lights. Prefer ½ cab shield.
- Provide bed floor tied downs in all four corners.
- Should include stake pockets and rub rail. Lights can be attached to bed/frame corner. Must not interfere with the sander. Three lights are required.
- Offer the option for 12" high side boards and/or 12" high fold down sides and tailgate.
- Tailgate should be double acting. No lower hinge, not a dump bed. Does not have to be removable but does need to pin in some manner.
- Improve bed pin system. Pins currently positioned same direction and fall out.
- Stop, tail turn and warning lights should be mounted at the rear of the bed in a way not to be hidden by a sander during winter operations. Physical mounting locations may vary between beds with drop sides.
- All hydraulic hose connections should be mounted on both sides of the bed facing out. Hoses and connectors must be mounted securely and protected. Current style of hose connectors.
- Stow away ladders are to be mounted to the outside. Do not use removable pin system to stow ladders.
- Bed is to be primed, painted and installed by vendor. Include pricing for an option to purchase the bed only which could be mounted by MoDOT forces.
- A license plate holder should be made available at the rear of the bed.
- Do not place advertisement stickers on bed.