

PREFERRED SPECIFICATIONS

Engines— 23 hp with oil filter and electric start. Engines governed to 3600 rpm.

Air Filter--Heavy-duty air canister.

Drive System—Two Hydro-Gear 10cc variable displacement pumps powering two high-efficiency Parker/Ross wheel motors with 1.0" diameter tapered shafts.

Ground Speed—0 mph to 6.2 mph forward, 0 to 2.2 mph reverse, infinitely variable.

Hydro Fluid—15w 50 Synthetic oil.

Cutting Deck—60" continuous seem welded 10-guage top and 7-guage skirt. 5"-deep, 4-point, full-floating deck with 6 adjustable anti-scalp rollers.

Cutting Height—1.5" to 4.5" in .5" increments.

Drive Tires—18 x 8.50-8, 4-ply Turf Master.

Caster Tires—11 x 3.50-4, 4-ply smooth tread.

Casters—Double-yoke, smooth tread caster wheel assembly with tire sealant.

Curb Weight—751 lbs.

Dimensions— FMD604

Width	Deflector up	61.4"	Deflector down	72.2"
	Length	83.4"	Height	45.0"

Blades—3-20.5" blades.

Blade-Tip Speed—18,000-18,500 fpm.

Blade Spindles—1.75" diameter mounted in cast aluminum alloy spindle housings with dual maintenance free bearings.

Engine Deck—7-Guage welded steel.

Turning Radius—True zero turn.

Drive-Wheel Release—Allows unit movement without engine running.

Fuel Capacity—Five gallons.

Electrical—12-volt battery with 15-amp alternator.

PTO Engagement—Electromagnetic clutch. 200 Ft Lb. 2 Year Warranty.

Hour Meter—Standard.

Safety Package—Operator Presence Controls (OPC). Operator must have speed control lever in neutral and blades disengaged to leave operator position without stopping engine.

Brake—Mechanical engagement integrated with OPC Safety System.

Accessories Available— StandOn Sulky