Missouri
Department
of Transportation

Kevin Keith, Director

105 West Capitol Avenue
P.O. Box 270
Jefferson City, MO 65102
(573) 751-2551
Fax (573) 751-6555
www.modot.org

ADDENDUM 003
REQUEST FOR BIDS
Multimodal Transit Vehicles
Request for Bid 3-121026TV

Bidders should acknowledge receipt of Addendum 003 (THREE) by **signing** and **including it** with the original bid. The due date for receipt of proposals remains **unchanged** by this Addendum. Accordingly, the following clarifications, questions and answers are believed to be of general interest to all potential Bidders. All other terms and conditions remain unchanged and in full force.

Name and Title of Signer (Print or type)	Name and Title of Department Authority Name Tom Veasman Title Sr. General Services Specialist
Contractor/Offeror Signature (Signature of person authorized to sign)	Department of Transportation Tom Veasman (Authorizing Signature)
Date Signed:	Date Signed: October 17, 2012

ADDENDUMS AND CLARIFICATIONS

TRANSIT VEHICLES 2013 MODEL YEAR

Light Duty Cutaway - Wide Body

1. Clarification - Body Exterior – Body width not to exceed 98", excluding wheel flares and mirrors.
2. Floor and Floor Covering – All exposed edges around the wall, doors and entranceway shall be trimmed with a molding securely attached providing a waterproof seal, or a waterproof sealant providing a waterproof seal.
3. Grabrails, Stanchions – All stanchions guardrails, grabhandles, and grabrails will be mounted to the floor or ceiling with at least four screws, or with at least two screws that are attached to steel mounted backing plates.

4. Clarification – Seating, Seat Belts, and Seating Arrangements - All retractable seat belts on the vehicle will have the same size male and female ends. All non-retractable seat belts on the vehicle will have the same size male and female ends.
5. Fold-A-Way Type Seat Requirements – All hardware to attach folding seats to the floor shall be recessed and/or positioned to prevent tripping and stumbling.
6. Clarification - Fold-A-Way Type Seat Requirements – Floor Plan GG – since this floor plan has no fixed seats, the minimum two (2) FMVSS 225 child seat restrain system latches will be located on two (2) separate fold-a-way seats,
7. Clarification – Fold-A-Way Type Seat Requirements – Floor Plan LL – This floor plan has two (2) fixed seats for two passengers each. If these two fixed seats together cannot each accommodate a FMVSS 225 latch position due to the presence of an Integrated Child Seat, then the second FMVSS 225 latch position may be located in a fold-a-way seat.
8. Clarification - Doors – Entrance RH – The bottom step of the stepwell may protrude below the door, but the door must incorporate a door sweep or flap on the bottom edge of the door.
9. Cooling – Type C hoses, fittings and clamps acceptable as long as they meet or exceed SAE specification J2064.