



Drake-Scruggs Equipment Inc.

Distributors of Truck and Utility Equipment

ADDITIONAL PROVISIONS

1. Occasions in which Drake-Scruggs Equipment Inc is to supply the cab and chassis for a customer it shall be invoiced to you upon delivery to Drake-Scruggs Equipment.
2. If, for any reason, delivery is not made within 10 days from the date specified, the cash selling price quoted herein will be subject to adjustment to conform to our regular cash selling price of the goods covered by this proposal in effect at the time of delivery. If the price adjustment results in an increase in price, you shall have the privilege of accepting delivery at the increased price or canceling your acceptance of this proposal by giving written notice of such cancellation to us within 5 days after notice of such price increase is given to you.
3. You agree to accept the goods covered by this proposal, as fulfilled thereof, with such changes in design and materials, or either of them, which we might make.
4. If any sales or excise taxes now in effect, shall be increased, or any new sales, excise, floor or processing taxes shall be imposed by federal, state, or local laws, you are to reimburse us for any and all such increased or new taxes that we may be required to pay or to reimburse to others by reason of the manufacture, purchase or sale of the articles and equipment covered by this proposal. The amount of such increased or new taxes may be billed as a separate item or added to the price of the articles and equipment to which they are applicable at our option.
5. We shall not be responsible for loss, damage, or delays in transportation after shipment, nor for failure to supply any goods covered by this proposal or to deliver the same on time where prevented by strikes, fires, or accidents, or by the demand exceeding the available supply, or by any other cause beyond our reasonable control.
6. Any cost incurred by Drake-Scruggs Equipment, Inc. as a result of either cancellation or change orders shall be passed to the buyer.

*Delivery time is only an estimate. This time may change due to unforeseen problems.

WARRANTY

DRAKE-SCRUGGS EQUIPMENT, INC. Warrants each new article to be free from defects in material and workmanship under normal use and service, its obligation under this warranty being limited to making good any part or parts thereof which shall be returned to it with transportation charges prepaid, and which its examination shall disclose to its satisfaction to have been thus defective, provided that such part or parts shall be so returned to it not later than (90) days after delivery of such article to the original purchaser. This warranty is expressly in lieu of all other warranties expressed or implied and of all other obligations or liabilities on its part, and it neither assumes nor authorizes any other person to assume for it any other liability in connection with the sale of its equipment.

This warranty shall not apply to any article which shall have been repaired or altered outside of its shop in any way so as, in its judgment, to affect its stability, nor which has been subject to misuse, negligence or accident. Warranty on all new equipment is subject to the individual manufacturer as attached.

Your Drake- Scruggs installed equipment is warranted from defects and workmanship for one year from the date of delivery. Included is one free field service trip within this warranty period. Normal travel charges will apply after this initial trip during the one year warranty period. After expiration of the one year warranty, normal travel, labor and material charges will apply. The one year warranty only applies to new components sold and installed by Drake-Scruggs Equipment Inc. Normal maintenance, repairs due to lack of maintenance and equipment transfers from chassis to chassis are not included in this warranty.

Aerial

VO-360X-MHI Insulated 60.3 ft. (18.4 m) overcenter, articulated material handling aerial platform lift

Full pressure turret mounted controls with override.

Continuous rotation including 3 slip ring for start/stop.

An eight gpm (30.4 lpm) open center hydraulic system with a 3000 psi (210 kg/cm²) system pressure.

Fiberglass upper boom tested per ANSI A92.2-1990 for Category C, 46 KV and below.

Chassis insulating system (lower boom insert) including accommodations to bridge insulation gap for testing per ANSI A92.2. Provides 12 in. (152 mm) insulation on VO-350 and 24 in (610 mm) on VO-355 and VO-360.

White urethane paint over a white gel coat on fiberglass upper boom and lower boom insert.

Two sets of hydraulic tool outlets, with 2,000 PSI pressure limit, at platform. Quick disconnect fittings are not included.

Two 1/2 in. (12.7 mm) diameter return lines.

External bulkhead reservoir (9.25 in. x 29.5 high in x 37 in. wide) with a 30 gallon (114 l) capacity, external filter, and sight level gauge.

90o platform rotation with hydraulic tilt at upper control for cleanout or rescue.

Full-length subframe and mounting hardware for 102-120 in. cab to axle chassis (subframe welded).

Lower Boom articulation is 125 degrees. Upper boom articulation is 210 degrees.

Boom stow cradle and ratchet type tie down strap and tubular platform supports.

Non-lube bearings.

Two operator's manuals and two service manuals (in English).

ANSI A92.2-1990 certification and data plate.

Lower control valve is standard.

Platform support providing 90 degree rotation. For use with single 1 man or two man platform.

Closed 24x48 two man platform with step towards pedestal.

24" x 48" Vinyl/Nylon platform cover.

24" x 48" X 42" platform liner with a step.

5' jib and winch with hydraulic extension. Includes 75' of 9/16" rope.

Manlift platform with maximum weight capacity of 600 lbs.

Maximum jib capacity.

Standard pedestal (40").

External bulkhead reservoir with a 30 gallon capacity. Mounted at the front of the cargo area.

Standard Category C 46KV and below electrical test band.

Emergency power insulated 12v DC hydraulic system. L

Auto lift throttle.

Standard 12v start/stop system.

5 pass collector ring assembly.

Two (2) Full body harness and lanyards (xtra large)

Aerial painted standard white to match chassis.

Main X-frame outriggers for 38-43" frame height. Mounted between the body and cab.

Auxiliary A-Frame outrigger for 37-43 inch frame height. Mounted at the rear of the body.

Outrigger valves with integral microswitches for outrigger motion alarm.

PTO and pump to power aerial hydraulic system.

Manufacturer's recommended amount of hydraulic oil to provide power to the unit.

Automatic boom latch.

Body

Knapheide steel line body including the following:

Overall Length: 147.25

Overall Width: 94

Pack Height: 50

Pack Depth: 18

Streetside Compartmentation:

1st Vertical - One (1) adjustable shelf with removable dividers on 4" centers

2nd Vertical - Six (6) adjustable locking swivel hooks. 2-2-2

3rd Vertical - Six (6) adjustable locking swivel hooks. 2-2-2

Horizontal - One (1) fixed shelf extending through to rear vertical.

Rear Vertical - Outrigger housing.

Curbside Compartmentation:

1st Vertical - One (1) adjustable shelf with removable dividers on 4" centers

2nd Vertical - Six (6) adjustable locking swivel hooks. 2-2-2

3rd Vertical - Gripstrut access steps with two sloped grab handles.

Horizontal - One (1) fixed shelf with removable dividers on 8" centers.

Rear Vertical - Five (5) fixed locking swivel hooks. Outrigger housing.

Additional Features:

- 24" tailshelf with 3" crossmembers and 3" high flatbar rail.

- Wheel chock holders, one each side in wheel wells.

- Outrigger pad holders.

- Master body lock system.

- Hotstick shelf, First vertical to rear on streetside only.

- Wooden tailboard at rear of body.

- Wooden tailboard at top of cargo access steps.

Heavy duty black dock bumpers 3.5" X 3.5" X 6". One each side of the frame at the rear. Extend chassis frame to rear to allow dock bumpers to protect pintle hook and glad hand connectors.

Two (2) heavy duty rubber wheel chocks with handles. Located in holders, one each side behind rear wheels.

Buyers model B30LXP Extra Heavy-Duty Mudflaps - 24x 30x 3/8".

Access steps with from cargo area to compartment top curbside.

Access steps with compartment top to bucket curbside.

Safety Equipment

Quote Number: 015413-0

Four (4) 24"x 24"x 2.25" wooden outrigger pads. Located in holders, one near each outrigger.

5 LB - ABC rated, fire extinguisher. Installed in street side vertical.

Triangle reflector kit. Shipped loose.

Dual Tone, 97 db, 12 to 24VDC warning back up alarm.

Non-skid material applied to all walking areas and top of compartments.

Large ball grounding stud for 3 point grounding system. Mounted at rear of chassis.

Three point grounding system tying unit, body and chassis to a common ground. Includes a grounding lug at the rear.

Towing Equipment

ICC bumper with two safety D-rings.

PH15 15 ton pintle hitch.

Chassis frame reinforcement for pintle hitch.

Six prong trailer socket installed at the rear of the unit adjacent to the pintle hitch location. (Plug will be wired to industry standard unless otherwise requested by customer)

Tekonsha brake controller.

Lighting

Ecco model 6750A amber round strobe light

Branch guard for 6750A

Elevated Pipe stand for strobe light.

Chassis

2013 International 4300 SBA 4x2 cab and chassis

Glad hands at rear, straight type.

Unit certification. Includes dielectric test, stability test, clean and weigh prior to pick up or delivery.

Quote Number: 015413-0

Total for One Unit	\$107,058.00
Chassis Price	\$68,742.00
Grand Total	\$175,800.00

If chassis is paid for at the time of delivery to Drake-Scruggs Equipment Inc., deduct \$700.00 from the above total price. *Title will be held until unit is paid in full*

FOB: FOB End User Location

State and municipal sales taxes are to be added if applicable.

FET shall be added if applicable.

Option 1

**Check Mark to Select This Option*

Primary and secondary 1-man buckets in lieu of single two man buckets. Each is 24x30 with 1 step towards the pedestal. Includes platform supports providing 90 degree rotation, two liners with step and 24x30 soft covers.

Additional access steps with compartment top to bucket streetside.

Additional set of access steps with from cargo area to compartment top streetside.

Secondary one man platform. 24x30 with 1 step towards the pedestal.

Add \$2,431.00

Option 2

**Check Mark to Select This Option*

Add air conditioning to 2012 International 4300.

Add \$553.00

Option 3

**Check Mark to Select This Option*

Add an AM/FM radio to 2012 International 4300.

Add \$205.00

Option 3

**Check Mark to Select This Option*

Time Mfg. 1 year extended warranty. (Two years total)

Add \$1,528.00

Option 5

**Check Mark to Select This Option*

Time Mfg. 2 year extended warranty. (Three years total)

Add \$3,234.00