



ITEM # 5 - New standard equipped 2007 / 2008 Model 1 Ton Chassis-Cab.With DRW

ACCEPTABLE MAKES AND MODELS:

- Standard Ford F-350 with 165" Wheelbase Cab to Axle 84"
- Standard Chevrolet/GMC C36403 with 161.5" Wheelbase Cab to Axle 84.9"
- Standard Dodge Ram 3500 with 167.5 Cab to Axle 84"

All units bid must contain the following options:

1. Standard minimum V8, diesel engine (Size _____ Horsepower _____)
2. 4-speed automatic transmission
3. Air conditioning
4. LH & RH manual trailer-type mirrors
5. Spare tire and wheel
6. Rubber floor mats
7. Minimum GVWR 11,000
8. Brakes 4-wheel anti-lock braking system (ABS)
9. Speed control and tilt wheel

DEALER COMPLETE IN DETAIL: I am bidding

2007(MAKE) _____ (MODEL) _____ GVWR _____ EACH \$ _____

2008 (MAKE) _____ (MODEL) _____ GVWR _____ EACH \$ _____

NET DELIVERED PRICE for One (1) new unit as described in Item 5 delivered to any of the listed delivery destinations (see page 67).

OPTIONAL EQUIPMENT PRICES, Item # 5

Indicate the additional cost or deduction for the below listed options. Prices should include all required options and special equipment.

**Option 5A. Mounted 11' platform body meeting Specification E1320.
\$ _____ (EACH) MAKE _____ MODEL _____**

**Option 5B. Permanently installed bulkhead to fit truck application (minimum requirement to top of cab).
\$ _____ (EACH)**

**Option 5C. Mounted 11' platform dump body meeting Specification E1327.
\$ _____ (EACH) (MAKE) _____ (MODEL) _____**

Option 5D. Provide live hydraulics with under hood clutch pump, tank with built in filter, 20 GPM 3 section valve assembly with power beyond, dual knob spreader valve and hoses for mounted dump body in specification E1335 or mounted platform body in specification E1327. This package shall be capable of driving the auger,



OPTIONAL EQUIPMENT PRICES, Item # 5 - Continued

spinner motor in an salt spreader, and power to raise angle plow. All hoses shall be provided from front to rear of truck.

\$_____ (EACH)

Option 5E. Mounted standard utility tool body. Acceptable makes and models are: Knapheide 6132D54J, Reading CLASSIC II 132A DW, Omaha 132D54V, Stahl CHALLENGER 132VVD-54. Body to include flush mounted tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess.

Submit descriptive literature and specifications showing exact service body you propose to furnish.

\$_____ (EACH) (MAKE) _____ (MODEL) _____

Option 5F. Six - 2" deep full width 250 lbs. capacity free sliding tool drawers mounted approximately 1 1/2" from top of compartment with approximately 2 1/2" between trays in lieu of two shelves and dividers in one of the full height vertical compartments.

\$_____ (EACH)

Option 5G. Two full length 250 lbs. capacity free sliding tool trays with metal dividers with slots on 4" centers with first tray mounted 5 1/4 " from bottom of compartment with approximately 1 1/2" between trays with second tray mounted above first in lieu of shelf and dividers in one of the horizontal compartments.

\$_____ (EACH)

Option 5H. One - full length (or from crane mounting point) 4" deep top opening compartment with release located inside side compartment, automatic up position latch and metal divider with slots on 4" centers in addition to the standard tool compartments. The top opening compartment will not protrude more than 2" into side compartment (The side compartment shall be 27" from floor to top of side body plus excess for flip top compartment).

\$_____ (EACH)

Option 5I. Minimum 25" high panel extension cover with minimum 42" locking rear doors which will provide a minimum 48" interior height for storage and work area.

\$_____ (EACH)

Option 5J. Body to have 3 section, tempered steel telescopic sliding roof and two piece, rigid aluminum, endgate cover to protect cargo area from weather and theft. A mechanical type seal will be placed on the telescopic sliding roof and endgate cover.

\$_____ (EACH)



OPTIONAL EQUIPMENT PRICES, Item # 5 - Continued

- Option 5K. Crane mount reinforced rigidly while maintaining full compartment space on top Rear corner of body either left or right for a 3500 lbs. capacity crane (with no mounting holes or bolt holes, we will drill to suit ourselves).
\$ _____ (EACH)
- Option 5L. One - double bottle gas drop well with minimum 55" clearance height (for large Bottle use) and retainers in lieu of the interior 48" full height vertical compartment.
\$ _____ (EACH)
- Option 5M. Four-wheel drive (state change in model).
\$ _____ (EACH) MODEL _____ (GVWR) _____
- Option 5N. Heavy-duty manual 5 or 6 speed transmission in lieu of automatic transmission.
\$ _____ (EACH) Deduct
- Option 5O. Allison automatic transmission.
\$ _____ (EACH)
- Option 5P. Heavy Duty, Type V with a Type III adapter trailer hitch. Special equipment which includes weight distributing hitch platform and wiring harness for an 7 pin commercial truck connector.
\$ _____ (EACH)
- Option 5Q. Exterior color to be Federal Standard #595B "Highway Yellow" #13432.
\$ _____ (EACH)
- Option 5R. Alternate diesel engine (state size and horsepower).
\$ _____ (EACH) SIZE _____ HORSEPOWER _____
- Option 5S. Standard gasoline engine in lieu of diesel engine (state size and horsepower).
\$ _____ (EACH) SIZE _____ HORSEPOWER _____
- Option 5T. Alternate gasoline engine in lieu of diesel engine (state size and horse power)
\$ _____ (EACH) SIZE _____ HORSEPOWER _____
- Option 5U. Single rear wheels (SWR) in lieu of dual rear wheel (DWR) (state GVWR).
\$ _____ (EACH) GVWR _____
- Option 5V. Snow plow package.
\$ _____ (EACH)



OPTIONAL EQUIPMENT PRICES, Item # 5 - Continued

Option 5W. Automatic transmission power take off provision.
\$ _____ (EACH)

Option 5X. 2 Factory cab steps. (one on Drivers Side, one on Passenger side)
\$ _____ (EACH)

Option 5Y. Alternative fuel in lieu of diesel. Acceptable engines are: E-85 Flex Fuel or Hybrid Electric.
\$ _____ (EACH) Fuel type _____ Engine _____ Size _____

Option 5Z. Hydraulic system to run body, plow and spreader, shall be all electric power line control design. In cab control modules to plug into cigar lighter for power, no wiring shall connect the in cab modules to the hydraulic valve assembly, which will be in an enclosure. The only common wiring shall be power and ground.
\$ _____ (EACH)

Option 5AA. Provide hydraulics and controls for dump hoist only
\$ _____ (EACH)

Please submit a complete parts list with detailed pricing information for each make/model your company would be willing to provide. Please indicate below the percent (%) discount off Manufacturers Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount _____

Delivery will be made approximately _____ days after receipt of order.