

**MAILING ADDRESS:**  
**MISSOURI DEPARTMENT OF TRANSPORTATION**  
**GENERAL SERVICES, P.O. BOX 270**  
**JEFFERSON CITY, MO 65102**

REQUEST NO.	3-131120TV
DATE	November 1, 2013

SEALED BIDS, SUBJECT TO THE ATTACHED CONDITIONS WILL BE RECEIVED AT THIS OFFICE UNTIL

**2:00 pm., Local Time, November 20, 2013**

AND THEN PUBLICLY OPENED AND READ FOR FURNISHING THE FOLLOWING EQUIPMENT.

**BIDS TO BE BASED F.O.B. MISSOURI DEPARTMENT OF TRANSPORTATION**

Submit net bid as cash discount stipulations will not be considered  
Various End User Delivery Locations

DEFINITE DELIVERY DATE SHOULD BE SHOWN. THE BIDDER MUST SIGN AND RETURN BEFORE DATE AND TIME SET FOR OPENING.

**BUYER:** Tom Veasman

**BUYER TELEPHONE:** 573-522-4404

**BUYER EMAIL:**

tom.veasman@modot.mo.gov

**MEDIUM DUTY VEHICLES**

This Request For Bid seeks bids from qualified organizations to provide vehicles in accordance with the following pages. MoDOT will receive bids at the following mailing address: P.O. Box 270, Jefferson City, MO 65102-0270, or hand-delivered in a sealed envelope to the following **physical address: General Services Procurement at 830 MoDOT Drive, Jefferson City, MO 65109** until 2:00 p.m., November 20, 2013. Bid forms and information may be obtained by contacting Tom Veasman at 573-522-4404, [tom.veasman@modot.mo.gov](mailto:tom.veasman@modot.mo.gov), or electronically download them at: <http://www.modot.org/business/surplus/Fleet%20Buyers%20Web%20Page/LightDutyTrucks.htm>

**Components of Agreement:** The Agreement between MHTC and the successful Bidder(s) shall consist of: the RFB and any written amendments thereto, the "Standard Bid Provisions, General Terms and Conditions and Special Terms and Conditions" that are attached to this RFB and the bid submitted by the Bidder in response to the RFB. However, MHTC reserves the right to clarify any relationship in writing and such written clarification shall govern in case of conflict with the applicable requirements stated in the RFB or the Bidder's bid. The Bidder is cautioned that its bid shall be subject to acceptance by MHTC without further clarification.

**Return sealed bid to the address shown at the top of this page.**

(SEE ATTACHED FOR TERMS, CONDITIONS, AND INSTRUCTIONS)

*In compliance with the above Request For Bid, and subject to all conditions thereof, the undersigned bidder agrees to furnish and deliver any or all the items on which prices were bid within the timeframe specified herein, after receipt of formal purchase order.*

**Date:** \_\_\_\_\_

**Firm Name:** \_\_\_\_\_

**Telephone No.:** \_\_\_\_\_

**Address:** \_\_\_\_\_

**Fax No.:** \_\_\_\_\_

**Federal I.D. No.** \_\_\_\_\_

**By (Signature):** \_\_\_\_\_

**Email Address:** \_\_\_\_\_

**Type/Print Name** \_\_\_\_\_

**Is your firm MBE certified?**  Yes  No

**Title:**  
**Is your firm WBE certified?**  Yes  No

# REVISED RFB (11/1/2013)

## 1. INTRODUCTION AND GENERAL INFORMATION

### 1.1 Introduction:

- 1.1.1 This Request for Bid (RFB) seeks bids from qualified organizations to provide medium duty trucks for the locations in the State of Missouri (See Section 2.4.2) through the end of the 2014 model year, to the Missouri Highways and Transportation Commission (MHTC) and Missouri Department of Transportation (MoDOT). Each bid must be in a sealed envelope, be mailed or delivered by courier to the RFB Coordinator at the below listed address, on or before the date and time listed herein for receipt of bids/proposals. All questions regarding the RFB shall be submitted to the RFB Coordinator. **Bids must be returned to the office of the RFB Coordinator no later than 2:00 p.m. CDT, November 20, 2013.**

#### RFB COORDINATOR:

**Tom Veasman, Senior General Services Specialist**

#### **MAILING ADDRESS:**

**Missouri Department of Transportation  
P. O. Box 270  
Jefferson City, MO 65102  
Attn: Tom Veasman**

#### **PHYSICAL ADDRESS:**

**Missouri Department of Transportation  
General Services Division  
830 MoDOT Drive  
Jefferson City, MO 65109**

**PHONE: 573-522-4404**

**FAX: 573-526-6948**

### 1.2 General Information:

- 1.2.1 This document constitutes an invitation for competitive, sealed bids for the procurement of medium duty trucks as set forth herein.
- 1.2.2 Organization: This RFB is divided into the following parts:
- 1) Introduction and General Information
  - 2) Scope of Work
  - 3) Bid Submission
  - 4) Pricing Page(s)
  - 5) Vendor Information and Preference Certification Form
  - 6) Notice Of Cooperative Purchasing
  - 7) Anti-Collusion Statement
  - 8) Terms and Conditions

## 2. SCOPE OF WORK

### 2.1 General Requirements:

- 2.1.1 The contractor shall provide medium duty trucks on an as needed, if needed basis for the MHTC and MoDOT, in accordance with the provisions and requirements stated herein.
- 2.1.2 The contractor shall provide all deliverables/services to the sole satisfaction of MoDOT.
- 2.1.3 MoDOT reserves the right to obtain “like or similar” products as specified herein from other Manufacturer’s, exclusive of the contract, when use of such products is deemed in the best interest of MoDOT.
- 2.1.4 Unless otherwise specified herein, the contractor shall furnish all material, labor, facilities, equipment, and supplies necessary to provide the deliverables/services required herein.
- 2.1.5 MoDOT reserves the right to reject any or all bids/quotes/proposals, and to accept or reject any items thereon, and to waive technicalities. In case of error in the extension of prices in the bid/quote/proposal, unit prices will govern.
- 2.1.6 This work is to be performed under the general supervision and direction of MoDOT and, if awarded any portion of the work, the Contractor agrees to furnish at his own expense all labor and equipment required to complete the work, it being expressly understood that this solicitation is for completed work based upon the price(s) specified and is not a solicitation for rental of equipment or employment of labor by MoDOT, and MoDOT is to have no direction or control over the employees used by the Contractor in performance of the work.

### 2.2 Required Specifications:

- a. All materials, equipment, and/or services bid upon must comply with the included MoDOT specifications and any other provisions outlined in the solicitation documents.

### 2.3 Delivery Requirements:

- 2.4.1 The following delivery requirements shall apply:
  - a. Unless otherwise specified on the solicitation documents or purchase order, suppliers shall give at least 24 hours advance notice of each delivery. Delivery will only be received between the hours of 8:00 a.m. to 3:00 p.m., Monday through Friday. No vehicles will be received on Saturday, Sunday or state holidays.
  - b. If the prices bid herein include the delivery cost of the material, the Contractor agrees to pay all transportation charges on the material as FOB - Destination. Freight costs must be included in the unit price bid and not listed as a separate line item.
  - c. Any demurrage is to be paid by the Contractor direct to the railroad or carrier.

2.4.2 The contractor shall deliver the products specified herein to the following MoDOT locations:

- a. St. Joseph, Missouri 64502
- b. Macon, Missouri 63552
- c. Hannibal, Missouri 63401
- d. Lee's Summit, Missouri 64064-8002
- e. Jefferson City, Missouri 65102
- f. Chesterfield, Missouri 63017-5712
- g. Joplin, Missouri 64802
- h. Springfield, Missouri 65801
- i. Willow Springs, Missouri 65793
- j. Sikeston, Missouri 63801

**2.5 Liquidated Damage Requirements:**

2.5.1 The bidder is directed to the "*Standard Bid Provisions, General Terms and Conditions and Special Terms and Conditions*" attached to the bid documents, regarding the amount and enforcement of liquidated damages.

**2.6 Contract/Purchase Order:**

2.6.1 The contract expresses the complete agreement of the parties and performance shall be governed solely by the specifications and requirements contained therein. Any change, whether by modification and/or supplementation, must be accomplished by a formal contract amendment signed and approved by and between the duly authorized representative of the Contractor and the duly authorized representative of the MHTC, by a modified purchase order prior to the effective date of such modification. The Contractor expressly and explicitly understands and agrees that no other method and/or no other document, including correspondence, acts, and oral communications by or from any person, shall be used or construed as an amendment or modification

**2.7 Invoicing and Payment Requirements:**

2.7.1 The contractor shall submit an itemized invoice to the applicable requesting address for the completion of deliverables, as specified herein.

2.7.2 Each invoice should be itemized in accordance with items listed on the purchase order and/or contract. The statewide financial management system has been designed to capture certain receipt and payment information. Therefore, each invoice submitted must reference the purchase order number and must be itemized in accordance with items listed on the purchase order. Failure to comply with this requirement may delay processing of invoices for payment.

2.7.3 The contractor shall be paid in accordance with the firm, fixed prices stated on the pricing page of this document after completion of deliverables specified herein and acceptance by MoDOT.

2.7.4 Other than the payment specified above, no other payments or reimbursements shall be made to the contractor for any reason whatsoever.

2.7.5 Unless otherwise provided for in the solicitation documents, payment for all equipment, supplies, and/or services required herein shall be made in arrears. The MHTC shall not make any advance deposits.

2.7.6 The MHTC assumes no obligation for equipment, supplies, and/or services shipped or provided in excess of the quantity ordered. Any authorized quantity is subject to the MHTC's rejection and shall be returned at the contractor's expense.

2.7.7 The MHTC reserves the right to purchase goods and services using the state-purchasing card.

## 2.8 Other Contractual Requirements:

- 2.8.1 Contract Period - The contract shall commence from the date of award until the end of the model year with up to two (2) one-year renewal option periods, or any portion therein. If the option for renewal is exercised by MoDOT, the contractor shall agree to all terms and conditions of the RFB and all subsequent amendments. Renewal options are at the sole discretion of MoDOT.
- 2.8.2 Escalation Clause - In the event the contractor requests a price increase during the contract period, either the original contract period or any contract renewal period, the contractor must provide a written request and documentation justifying the need for a price increase, and the amount of such price increase. MoDOT will review the contractor's written request and documentation, and decide if a price increase is to be granted at that particular time. The contractor shall understand and agree that MoDOT's decision shall be final and without recourse.
- a. No price increase shall be granted during the first 3 months of the original contract period, or if applicable, first 3 months of a contract renewal period.
- 2.8.3 Inspection and Acceptance: MoDOT reserves the right to inspect the material at the point of manufacture, intermediate storage point, or at a destination which shall be at the discretion of MoDOT.
- a. No equipment, supplies, and/or services received by MoDOT pursuant to a contract shall be deemed accepted until MoDOT has had reasonable opportunity to inspect said equipment, supplies, and/or services.
- b. All equipment, supplies, and/or services which do not comply with the specifications and/or requirements or which are otherwise unacceptable or defective may be rejected. In addition, all equipment, supplies, and/or services which are discovered to be defective or which do not conform to any warranty of the Contractor upon inspection (or at any later time if the defects contained were not reasonably ascertainable upon the initial inspection) may be rejected.
- c. The MHTC reserves the right to return any such rejected shipment at the Contractor's expense for full credit or replacement and to specify a reasonable date by which replacements must be received.
- d. The MHTC's right to reject any unacceptable equipment, supplies, and/or services shall not exclude any other legal, equitable or contractual remedies the MHTC may have.
- a. The bidder is directed to the "*Standard Bid Provisions, General Terms and Conditions and Special Terms and Conditions*" attached to the bid documents, regarding the amount and types of insurance certificates required to be submitted by the contractor.
- 2.8.4 NET DELIVERED FIRM PRICE - the unit(s) shall be delivered complete and ready for use to the delivery destinations.

### 3. BID SUBMISSION

#### 3.1 Bid Submission Information:

- 3.1.1 All bids must be received in a sealed envelope/packaging clearly marked “3-131120TV Medium Duty Trucks”.
- 3.1.2 All bids must be received at the office of the RFB Coordinator as outlined in Section 1. “INTRODUCTION AND GENERAL INFORMATION”.
- 3.1.3 The bidder may withdraw, modify or correct his/her bid after it has been deposited with MoDOT provided such request is submitted in writing and received at the location designated for the bid opening prior to the date and time specified for opening bids. Such a request received as specified will be attached to the bid and the bid will be considered to have been modified accordingly. No bid may be modified after the date and time specified for the opening of bids.
- 3.1.4 Open Competition / Request For Bid Document:
- a. It shall be the bidder's responsibility to ask questions, request changes or clarification, or otherwise advise MoDOT if any language, specifications or requirements of an RFB appear to be ambiguous, contradictory, and/or arbitrary, or appear to inadvertently restrict or limit the requirements stated in the RFB to a single source. Any and all communication from bidders regarding specifications, requirements, competitive bid process, etc., must be directed to the buyer from MoDOT, unless the RFB specifically refers the bidder to another contact. Such communication should be received at least three (3) working days prior to the official bid opening date.
  - b. Every attempt shall be made to ensure that the bidder receives an adequate and prompt response. However, in order to maintain a fair and equitable bid process, all bidders will be advised, via the issuance of an amendment to the RFB, of any relevant or pertinent information related to the procurement. Therefore, bidders are advised that unless specified elsewhere in the RFB, any questions received less than three (3) working days prior to the RFB opening date may not be answered.
  - c. Bidders are cautioned that the only official position of the MoDOT is that which is issued by MoDOT in the RFB or an amendment thereto. No other means of communication, whether oral or written, shall be construed as a formal or official response or statement.
  - d. MoDOT monitors all procurement activities to detect any possibility of deliberate restraint of competition, collusion among bidders, price-fixing by bidders, or any other anticompetitive conduct by bidders which appears to violate state and federal antitrust laws. Any suspected violation shall be referred to the Missouri Attorney General's Office for appropriate action.
- 3.1.5 Bid Review: Bids will be reviewed to determine if the bid complies with the mandatory requirements, and to determine the lowest and best bid.
- 3.1.6 Cost Determination: The low bid shall be determined by adding all of the prices on the pricing pages for the original contract period.
- 3.1.7 Contract Award: This is a Multiple Award bid and there will be no ‘one’ bidder awarded each item within this bid. Each individual delivery destination will have sole responsibility for the discretion of all purchasing decisions. Criteria used to determine purchasing decisions are price, location of servicing dealers, past performance of servicing dealers, and past performance of different makes and models.
- a. Notification of award shall be at the time the tabulation is posted to the Internet. It is the sole responsibility for all bidders to check the website for bid results.

**ITEM # 1 - NEW STANDARD EQUIPPED 2014 OR NEWER MODEL 2WD REGULAR CAB ¾ TON PICKUP.**

**ACCEPTABLE MAKES AND MODELS:**

Standard Ford F-250 with 137" Wheelbase, Cab to Axle 56"  
Standard Chevrolet 2500 with 133" Wheelbase, Cab to Axle 56"  
Standard Dodge 2500 with 140" Wheelbase, Cab to Axle 56"

**\*This item number is not recommended for a plow\***

**All units bid must contain the following options:**

1. Standard, minimum V8 fuel-injected gasoline engine (Size \_\_\_\_\_ Horsepower \_\_\_\_\_)
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds \_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(4) manufacturer's standard all season, plus full size spare and wheel (Size \_\_\_\_\_)
7. Minimum 8,600 lbs. GVWR
8. Heavy-duty (Type III) trailer package to include receiver hitch
9. 8' Bed
10. Brakes, 4-wheel anti-lock braking system (ABS)
11. Speed control and tilt wheel
12. Rubber Flooring
13. Vinyl seats
14. 3 sets of keys

**DEALER COMPLETE:**

2014 MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ FUEL CAPACITY \_\_\_\_\_ OIL CAPACITY \_\_\_\_\_

IS THIS ENGINE E-85 COMPATIBLE? \_\_\_\_\_ IF SO WHAT IS E-85 MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_

BUMPER TO BUMPER WARRANTY \_\_\_\_\_

POWERTRAIN WARRANTY \_\_\_\_\_

EXTENDED WARRANTY \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 1**

Indicate the additional cost or deduction for the below listed options, which should include all required options and special equipment.

Option 1A. Heavy-duty manual transmission in lieu of automatic transmission EACH \$ \_\_\_\_\_

Option 1B. Exterior color to be Federal Standard #595B "Highway Yellow" EACH \$ \_\_\_\_\_

Option 1C. Standard diesel engine in lieu of gasoline engine (state size and horsepower)  
SIZE \_\_\_\_\_ HORSEPOWER \_\_\_\_\_ EACH \$ \_\_\_\_\_

Option 1D. CNG engine in lieu of gasoline engine (provide the following information) EACH \$ \_\_\_\_\_

ENGINE: SIZE \_\_\_\_\_ HP \_\_\_\_\_ MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

TRANSMISSION: MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

CNG TANK: DGE CAPACITY \_\_\_\_\_ TANK LOCATION \_\_\_\_\_

- Option 1E. 2 Full length cab steps or running boards.  
(one on drivers side, one on passenger side) SET \$ \_\_\_\_\_
- Option 1F. Power windows and power door locks EACH \$ \_\_\_\_\_
- Option 1G. Bluetooth Capability EACH \$ \_\_\_\_\_
- Option 1H. Optional Rear Axle Ratio Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 1I. Limited Slip Rear Axle Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 1J. Commercial grade spray on bed lining to be applied on floors,  
sides, front, tailgate and top of rail. EACH \$ \_\_\_\_\_
- Option 1K. Electric Trailer Brake Controller EACH \$ \_\_\_\_\_
- Option 1L. Bed delete(cab and chassis with spare wheel and tire, and no receiver hitch) EACH \$ \_\_\_\_\_ (Deduct)
- Option 1M.1 Mounted 8' platform body meeting Specification E1320SRW EACH \$ \_\_\_\_\_  
MAKE \_\_\_\_\_ MODEL \_\_\_\_\_
- Option 1M.2 Mounted 8' aluminum platform body meeting Specification E1320SRW EACH \$ \_\_\_\_\_  
(Minimum 1" aluminum extruded floor instead of steel)  
MAKE \_\_\_\_\_ MODEL \_\_\_\_\_
- Option 1N. Permanently installed bulkhead to fit truck application EACH \$ \_\_\_\_\_  
(Minimum requirement to top of cab)
- Option 1O. Mounted standard utility tool body. EACH \$ \_\_\_\_\_

Acceptable makes and models are:

Knapheide 696J	Stahl CHALLENGER II 96VVS - 48.5
Reading Classic II 98A S.W.	RKI -L5680
Omaha 96V	RKI L5780 (for Dodge)

Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

- Option 1P. Utility tool body 3 section, tempered steel telescopic sliding roof and two-piece rigid aluminum end gate cover to protect cargo area from weather and theft. EACH \$ \_\_\_\_\_
- Option 1Q. Heavy duty, Class V (2-1/2" square tube) receiver trailer hitch. EACH \$ \_\_\_\_\_  
Includes an adapter to reduce to 2" (Class III/IV) and a seven-wire RV style trailer plug (needed if ordering bed delete)

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_

Delivery will be made approximately \_\_\_\_\_ days after receipt of order.

**ITEM # 2 - New standard equipped 2014 or Newer Model 2WD Extended Cab ¾ Ton Pickup.**

**ACCEPTABLE MAKES AND MODELS:**

Standard Ford F-250 with 158" Wheelbase, Cab to Axle 56"  
Standard Chevrolet 2500 with 158" Wheelbase, Cab to Axle 56"  
Standard Dodge 2500 with 168" Wheelbase, Cab to Axle 56"

**\*This item number is not recommended for a plow\***

**All units bid must contain the following options:**

1. Standard, minimum V8 fuel-injected gasoline engine (Size \_\_\_\_\_ Horsepower \_\_\_\_\_)
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds \_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(4) manufacturer's standard all season, plus full size spare and wheel (Size \_\_\_\_\_)
7. Minimum 8,600 lbs. GVWR
8. Heavy-duty (Type III) trailer package to include receiver hitch
9. 8' Bed
10. Brakes, 4-wheel anti-lock braking system (ABS)
11. Speed control and tilt wheel
12. Rubber Flooring
13. Vinyl seats

**DEALER COMPLETE:**

2014 MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ FUEL CAPACITY \_\_\_\_\_ OIL CAPACITY \_\_\_\_\_

IS THIS ENGINE E-85 COMPATIBLE? \_\_\_\_\_ IF SO WHAT IS E-85 MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_

BUMPER TO BUMPER WARRANTY \_\_\_\_\_

POWERTRAIN WARRANTY \_\_\_\_\_

EXTENDED WARRANTY \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 2**

Indicate the additional cost or deduction for the below listed options, which should include all required options and special equipment.

Option 2A. Heavy-duty manual transmission in lieu of automatic transmission EACH \$ \_\_\_\_\_

Option 2B. Exterior color to be Federal Standard #595B "Highway Yellow" EACH \$ \_\_\_\_\_

Option 2C. Standard diesel engine in lieu of gasoline engine (state size/horsepower) EACH \$ \_\_\_\_\_

SIZE \_\_\_\_\_ HORSEPOWER \_\_\_\_\_

Option 2D. CNG engine in lieu of gasoline engine (provide the following information) EACH \$ \_\_\_\_\_

ENGINE: SIZE \_\_\_\_\_ HP \_\_\_\_\_ MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

TRANSMISSION: MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

CNG TANK: DGE CAPACITY \_\_\_\_\_ TANK LOCATION \_\_\_\_\_

Option 2E. 2 Full length cab steps or running boards. SET \$ \_\_\_\_\_  
(One on drivers side, one on passenger side)

- Option 2F. Power windows and power door locks EACH \$ \_\_\_\_\_
- Option 2G. Bluetooth Capability EACH \$ \_\_\_\_\_
- Option 2H. Optional Rear Axle Ratio Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 2I. Limited Slip Rear Axle Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 2J. 6 ½ foot bed in lieu of 8 foot bed EACH \$ \_\_\_\_\_ (Deduct)
- Option 2K. Commercial grade spray on bed lining to be applied on floors, sides, front, tailgate and top of rail. EACH \$ \_\_\_\_\_
- Option 2L. Electric Trailer Brake Controller EACH \$ \_\_\_\_\_
- Option 2M. Bed delete(cab and chassis with spare wheel and tire, and no receiver hitch) EACH \$ \_\_\_\_\_ (Deduct)
- Option 2N.1 Mounted 8' platform body meeting Specification E1320SRW EACH \$ \_\_\_\_\_  
MAKE \_\_\_\_\_ MODEL \_\_\_\_\_
- Option 2N.2 Mounted 8' aluminum platform body meeting Specification E1320SRW (Minimum 1" aluminum extruded floor instead of steel) EACH \$ \_\_\_\_\_  
MAKE \_\_\_\_\_ MODEL \_\_\_\_\_
- Option 2O. Permanently installed bulkhead to fit truck application (Minimum requirement to top of cab) EACH \$ \_\_\_\_\_
- Option 2P. Mounted standard utility tool body. EACH \$ \_\_\_\_\_

Acceptable makes and models are:

Knapheide 696J	Stahl CHALLENGER II 96VVS - 48.5
Reading Classic II 98A S.W.	RKI -L5680
Omaha 96V	RKI L5780 (for Dodge)

Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

- Option 2Q. Utility tool body 3 section, tempered steel telescopic sliding roof and two-piece rigid aluminum end gate cover to protect cargo area from weather and theft EACH \$ \_\_\_\_\_
- Option 2R. Heavy duty, Class V (2-1/2" square tube) receiver trailer hitch. Includes an adapter to reduce to 2" (Class III/IV) and a seven-wire RV style trailer plug (needed if ordering bed delete, Option 2M) EACH \$ \_\_\_\_\_

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_

Delivery will be made approximately \_\_\_\_\_ days after receipt of order.

**ITEM # 3 - New standard equipped 2014 or Newer Model 2WD Crew Cab ¾ Ton Pickup.**

**ACCEPTABLE MAKES AND MODELS:**

Standard Ford F-250 with 172" Wheelbase, Cab to Axle 56"  
Standard Chevrolet 2500 with 172" Wheelbase, Cab to Axle 56"  
Standard Dodge 2500 with 168" Wheelbase, Cab to Axle 56"

**\*This item number is not recommended for a plow\***

**All units bid must contain the following options:**

1. Standard, minimum V8 fuel-injected gasoline engine (Size \_\_\_\_\_ Horsepower \_\_\_\_\_)
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds \_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(4) manufacturer's standard all season, plus full size spare and wheel (Size \_\_\_\_\_)
7. Minimum 8,600 lbs. GVWR
8. Heavy-duty (Type III) trailer package to include receiver hitch
9. 8' Bed
10. Brakes, 4-wheel anti-lock braking system (ABS)
11. Speed control and tilt wheel
12. Rubber Flooring
13. Vinyl seats
14. 3 sets of keys

**DEALER COMPLETE:**

2014 MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ FUEL CAPACITY \_\_\_\_\_ OIL CAPACITY \_\_\_\_\_

IS THIS ENGINE E-85 COMPATIBLE? \_\_\_\_\_ IF SO WHAT IS E-85 MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_

BUMPER TO BUMPER WARRANTY \_\_\_\_\_

POWERTRAIN WARRANTY \_\_\_\_\_

EXTENDED WARRANTY \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 3**

Indicate the additional cost or deduction for the below listed options, which should include all required options and special equipment.

Option 3A. Heavy-duty manual transmission in lieu of automatic transmission EACH \$ \_\_\_\_\_

Option 3B. Exterior color to be Federal Standard #595B "Highway Yellow" EACH \$ \_\_\_\_\_

Option 3C. Standard diesel engine in lieu of gasoline engine (state size and horsepower)  
SIZE \_\_\_\_\_ HORSEPOWER \_\_\_\_\_ EACH \$ \_\_\_\_\_

Option 3D. CNG engine in lieu of gasoline engine (provide the following information) EACH \$ \_\_\_\_\_  
ENGINE: SIZE \_\_\_\_\_ HP \_\_\_\_\_ MAKE \_\_\_\_\_ MODEL \_\_\_\_\_  
TRANSMISSION: MAKE \_\_\_\_\_ MODEL \_\_\_\_\_  
CNG TANK: DGE CAPACITY \_\_\_\_\_ TANK LOCATION \_\_\_\_\_

Option 3E. 2 Full length cab steps or running boards. SET \$ \_\_\_\_\_  
(One on drivers side, one on passenger side)

- Option 3F. Power windows and power door locks EACH \$ \_\_\_\_\_
- Option 3G. Bluetooth Capability EACH \$ \_\_\_\_\_
- Option 3H. Optional Rear Axle Ratio Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 3I. Limited Slip Rear Axle Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 3J. 6 ½ foot bed in lieu of 8 foot bed EACH \$ \_\_\_\_\_ (Deduct)
- Option 3K. Commercial grade spray on bed lining to be applied on floors, sides, front, tailgate and top of rail. EACH \$ \_\_\_\_\_
- Option 3L. Electric Trailer Brake Controller EACH \$ \_\_\_\_\_
- Option 3M. Bed delete(cab and chassis with spare wheel and tire, and no receiver hitch) EACH \$ \_\_\_\_\_ (Deduct)
- Option 3N.1 Mounted 8' platform body meeting Specification E1320SRW EACH \$ \_\_\_\_\_  
MAKE \_\_\_\_\_ MODEL \_\_\_\_\_
- Option 3N.2 Mounted 8' aluminum platform body meeting Specification E1320SRW EACH \$ \_\_\_\_\_  
(Minimum 1" aluminum extruded floor instead of steel)  
MAKE \_\_\_\_\_ MODEL \_\_\_\_\_
- Option 3O. Permanently installed bulkhead to fit truck application EACH \$ \_\_\_\_\_  
(Minimum requirement to top of cab)
- Option 3P. Mounted standard utility tool body. EACH \$ \_\_\_\_\_
- Acceptable makes and models are:
- |                             |                                  |
|-----------------------------|----------------------------------|
| Knapheide 696J              | Stahl CHALLENGER II 96VVS - 48.5 |
| Reading Classic II 98A S.W. | RKI -L5680                       |
| Omaha 96V                   | RKI L5780 (for Dodge)            |
- Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess
- MAKE \_\_\_\_\_ MODEL \_\_\_\_\_
- Option 3Q. Utility tool body 3 section, tempered steel telescopic sliding roof and two-piece rigid aluminum end gate cover to protect cargo area from weather and theft EACH \$ \_\_\_\_\_
- Option 3R. Heavy duty, Class V (2-1/2" square tube) receiver trailer hitch. EACH \$ \_\_\_\_\_  
Includes an adapter to reduce to 2" (Class III/IV) and a seven-wire RV style trailer plug (needed if ordering bed delete, Option 3M)

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

*% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_*

Delivery will be made approximately \_\_\_\_\_ days after receipt of order.

**ITEM # 4 - New standard equipped 2014 or Newer Model 4WD Regular Cab ¾ Ton Pickup.**

**ACCEPTABLE MAKES AND MODELS:**

Standard Ford F-250 with 137" Wheelbase, Cab to Axle 56"  
Standard Chevrolet 2500 with 133" Wheelbase, Cab to Axle 56"  
Standard Dodge 2500 with 140" Wheelbase, Cab to Axle 56"

**All units bid must contain the following options:**

1. Standard, minimum V8 fuel-injected gasoline engine (Size\_\_\_\_\_ Horsepower\_\_\_\_\_)
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds\_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(4) manufacturer's standard all season, plus full size spare and wheel (Size\_\_\_\_\_)
7. Minimum 8,600 lbs. GVWR
8. Heavy-duty (Type III) trailer package to include receiver hitch
9. 8' Bed
10. Brakes, 4-wheel anti-lock braking system (ABS)
11. Speed control and tilt wheel
12. Rubber Flooring
13. Vinyl seats
14. 3 sets of keys

**DEALER COMPLETE:**

2014 MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ FUEL CAPACITY \_\_\_\_\_ OIL CAPACITY \_\_\_\_\_

IS THIS ENGINE E-85 COMPATIBLE? \_\_\_\_\_ IF SO WHAT IS E-85 MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_

BUMPER TO BUMPER WARRANTY \_\_\_\_\_

POWERTRAIN WARRANTY \_\_\_\_\_

EXTENDED WARRANTY \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 4**

Indicate the additional cost or deduction for the below listed options, which should include all required options and special equipment.

Option 4A. Heavy-duty manual transmission in lieu of automatic transmission EACH \$ \_\_\_\_\_

Option 4B. Exterior color to be Federal Standard #595B "Highway Yellow" EACH \$ \_\_\_\_\_

Option 4C. Standard diesel engine in lieu of gasoline engine EACH \$ \_\_\_\_\_  
(State size and horsepower)

SIZE \_\_\_\_\_ HORSEPOWER \_\_\_\_\_

Option 4D. CNG engine in lieu of gasoline engine (provide the following information) EACH \$ \_\_\_\_\_

ENGINE: SIZE \_\_\_\_\_ HP \_\_\_\_\_ MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

TRANSMISSION: MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

CNG TANK: DGE CAPACITY \_\_\_\_\_ TANK LOCATION \_\_\_\_\_

Option 4E. 2 Full length cab steps or running boards. SET \$ \_\_\_\_\_  
(One on drivers side, one on passenger side)

- Option 4F. Power windows and power door locks EACH \$ \_\_\_\_\_
- Option 4G. Bluetooth Capability EACH \$ \_\_\_\_\_
- Option 4H. Optional Rear Axle Ratio Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 4I. Limited Slip Rear Axle Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 4J. Commercial grade spray on bed lining to be applied on floors, sides, front, tailgate and top of rail. EACH \$ \_\_\_\_\_
- Option 4K. Electric Trailer Brake Controller EACH \$ \_\_\_\_\_
- Option 4L. Bed delete(cab and chassis with spare wheel and tire, and no receiver hitch) EACH \$ \_\_\_\_\_ (Deduct)
- Option 4M.1 Mounted 8' platform body meeting Specification E1320SRW EACH \$ \_\_\_\_\_  
MAKE \_\_\_\_\_ MODEL \_\_\_\_\_
- Option 4M.2 Mounted 8' aluminum platform body meeting Specification E1320SRW (Minimum 1" aluminum extruded floor instead of steel) EACH \$ \_\_\_\_\_  
MAKE \_\_\_\_\_ MODEL \_\_\_\_\_
- Option 4N. Permanently installed bulkhead to fit truck application (Minimum requirement to top of cab) EACH \$ \_\_\_\_\_
- Option 4O. Mounted standard utility tool body. EACH \$ \_\_\_\_\_  
Acceptable makes and models are:  
Knapheide 696J Stahl CHALLENGER II 96VVS - 48.5  
Reading Classic II 98A S.W. RKI -L5680  
Omaha 96V RKI L5780 (for Dodge)
- Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess  
MAKE \_\_\_\_\_ MODEL \_\_\_\_\_
- Option 4P. Utility tool body 3 section, tempered steel telescopic sliding roof and two-piece rigid aluminum endgate cover to protect cargo area from weather and theft EACH \$ \_\_\_\_\_
- Option 4Q. Heavy duty, Class V (2-1/2" square tube) receiver trailer hitch. Includes an adapter to reduce to 2" (Class III/IV) and a seven-wire RV style trailer plug (needed if ordering bed delete, Option 4L) EACH \$ \_\_\_\_\_

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

*% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_*

Delivery will be made approximately \_\_\_\_\_ days after receipt of order.

**ITEM #5** - New standard equipped **2014 or Newer Model 4WD Extended Cab ¾ Ton Pickup.**

**ACCEPTABLE MAKES AND MODELS:**

Standard Ford F-250 with 158" Wheelbase, Cab to Axle 56"  
Standard Chevrolet 2500 with 158" Wheelbase, Cab to Axle 56"  
Standard Dodge 2500 with 168" Wheelbase, Cab to Axle 56"

**All units bid must contain the following options:**

1. Standard, minimum V8 fuel-injected gasoline engine (Size \_\_\_\_\_ Horsepower \_\_\_\_\_)
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds \_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(4) manufacturer's standard all season, plus full size spare and wheel (Size \_\_\_\_\_)
7. Minimum 8,600 lbs. GVWR
8. Heavy-duty (Type III) trailer package to include receiver hitch
9. 8' Bed
10. Brakes, 4-wheel anti-lock braking system (ABS)
11. Speed control and tilt wheel
12. Rubber Flooring
13. Vinyl seats
14. 3 sets of keys

**DEALER COMPLETE:**

2014 MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ FUEL CAPACITY \_\_\_\_\_ OIL CAPACITY \_\_\_\_\_

IS THIS ENGINE E-85 COMPATIBLE? \_\_\_\_\_ IF SO WHAT IS E-85 MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_

BUMPER TO BUMPER WARRANTY \_\_\_\_\_

POWERTRAIN WARRANTY \_\_\_\_\_

EXTENDED WARRANTY \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 5**

Indicate the additional cost or deduction for the below listed options, which should include all required options and special equipment.

Option 5A. Heavy-duty manual transmission in lieu of automatic transmission EACH \$ \_\_\_\_\_

Option 5B. Exterior color to be Federal Standard #595B "Highway Yellow" EACH \$ \_\_\_\_\_

Option 5C. Standard diesel engine in lieu of gasoline engine (state size/horsepower) EACH \$ \_\_\_\_\_

SIZE \_\_\_\_\_ HORSEPOWER \_\_\_\_\_

Option 5D. CNG engine in lieu of gasoline engine (provide the following information) EACH \$ \_\_\_\_\_

ENGINE: SIZE \_\_\_\_\_ HP \_\_\_\_\_ MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

TRANSMISSION: MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

CNG TANK: DGE CAPACITY \_\_\_\_\_ TANK LOCATION \_\_\_\_\_

Option 5E. 2 Full length cab steps or running boards. SET \$ \_\_\_\_\_  
(One on drivers side, one on passenger side)

- Option 5F. Power windows and power door locks EACH \$ \_\_\_\_\_
- Option 5G. Optional Rear Axle Ratio Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 5H. Limited Slip Rear Axle Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 5I. 6 ½ foot bed in lieu of 8 foot bed EACH \$ \_\_\_\_\_ (Deduct)
- Option 5J. Commercial grade spray on bed lining to be applied on floors, sides, front, tailgate and top of rail. EACH \$ \_\_\_\_\_
- Option 5K. Electric Trailer Brake Controller EACH \$ \_\_\_\_\_
- Option 5L. Bluetooth Capability EACH \$ \_\_\_\_\_
- Option 5M. Bed delete(cab and chassis with spare wheel and tire, and no receiver hitch) EACH \$ \_\_\_\_\_ (Deduct)
- Option 5N.1 Mounted 8' platform body meeting Specification E1320SRW EACH \$ \_\_\_\_\_  
MAKE \_\_\_\_\_ MODEL \_\_\_\_\_
- Option 5N.2 Mounted 8' aluminum platform body meeting Specification E1320SRW (Minimum 1" aluminum extruded floor instead of steel) EACH \$ \_\_\_\_\_  
MAKE \_\_\_\_\_ MODEL \_\_\_\_\_
- Option 5O. Permanently installed bulkhead to fit truck application (minimum requirement to top of cab) EACH \$ \_\_\_\_\_
- Option 5P. Mounted standard utility tool body. EACH \$ \_\_\_\_\_
- Acceptable makes and models are:
- |                             |                                  |
|-----------------------------|----------------------------------|
| Knapeheide 696J             | Stahl CHALLENGER II 96VVS - 48.5 |
| Reading Classic II 98A S.W. | RKI -L5680                       |
| Omaha 96V                   | RKI L5780 (for Dodge)            |
- Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess
- MAKE \_\_\_\_\_ MODEL \_\_\_\_\_
- Option 5Q. Utility tool body 3 section, tempered steel telescopic sliding roof and two-piece rigid aluminum endgate cover to protect cargo area from weather and theft EACH \$ \_\_\_\_\_
- Option 5R. Heavy duty, Class V (2-1/2" square tube) receiver trailer hitch. Includes an adapter to reduce to 2" (Class III/IV) and a seven-wire RV style trailer plug (needed if ordering bed delete, Option 5M) EACH \$ \_\_\_\_\_

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

*% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_*

Delivery will be made approximately \_\_\_\_\_ days after receipt of order.

**ITEM # 6 - New standard equipped 2014 or Newer Model 4WD Crew Cab ¾ Ton Pickup.**

**ACCEPTABLE MAKES AND MODELS:**

Standard Ford F-250 with 172" Wheelbase, Cab to Axle 56"  
Standard Chevrolet 2500 with 167" Wheelbase, Cab to Axle 56"  
Standard Dodge 2500 with 168" Wheelbase, Cab to Axle 56"

**All units bid must contain the following options:**

1. Standard, minimum V8 fuel-injected gasoline engine (Size\_\_\_\_\_ Horsepower\_\_\_\_\_)
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds\_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(4) manufacturer's standard all season, plus full size spare and wheel (Size\_\_\_\_\_)
7. Minimum 8,600 lbs. GVWR
8. Heavy-duty (Type III) trailer package to include receiver hitch
9. 8' Bed
10. Brakes, 4-wheel anti-lock braking system (ABS)
11. Speed control and tilt wheel
12. Rubber Flooring
13. Vinyl seats
14. 3 sets of keys

**DEALER COMPLETE:**

2014 MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ FUEL CAPACITY \_\_\_\_\_ OIL CAPACITY \_\_\_\_\_

IS THIS ENGINE E-85 COMPATIBLE? \_\_\_\_\_ IF SO WHAT IS E-85 MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_

BUMPER TO BUMPER WARRANTY \_\_\_\_\_

POWERTRAIN WARRANTY \_\_\_\_\_

EXTENDED WARRANTY \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 6**

Indicate the additional cost or deduction for the below listed options, which should include all required options and special equipment.

Option 6A. Heavy-duty manual transmission in lieu of automatic transmission EACH \$ \_\_\_\_\_

Option 6B. Exterior color to be Federal Standard #595B "Highway Yellow" EACH \$ \_\_\_\_\_

Option 6C. Standard diesel engine in lieu of gasoline engine (state size/horsepower) EACH \$ \_\_\_\_\_

SIZE \_\_\_\_\_ HORSEPOWER \_\_\_\_\_

Option 6D. CNG engine in lieu of gasoline engine (provide the following information) EACH \$ \_\_\_\_\_

ENGINE: SIZE \_\_\_\_\_ HP \_\_\_\_\_ MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

TRANSMISSION: MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

CNG TANK: DGE CAPACITY \_\_\_\_\_ TANK LOCATION \_\_\_\_\_

Option 6E. 2 Full length cab steps or running boards. SET \$ \_\_\_\_\_  
(One on drivers side, one on passenger side)

- Option 6E. Power windows and power door locks EACH \$ \_\_\_\_\_
- Option 6F. Bluetooth Capability EACH \$ \_\_\_\_\_
- Option 6G. Optional Rear Axle Ratio Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 6H. Limited Slip Rear Axle Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 6I. 6 1/2 foot bed in lieu of 8 foot bed EACH \$ \_\_\_\_\_ (Deduct)
- Option 6J. Commercial grade spray on bed lining to be applied on floors, sides, front, tailgate and top of rail. EACH \$ \_\_\_\_\_
- Option 6K. Electric Trailer Brake Controller EACH \$ \_\_\_\_\_
- Option 6L. Bed delete(cab and chassis with spare wheel and tire, and no receiver hitch) EACH \$ \_\_\_\_\_ (Deduct)
- Option 6M.1 Mounted 8' platform body meeting Specification E1320SRW EACH \$ \_\_\_\_\_  
MAKE \_\_\_\_\_ MODEL \_\_\_\_\_
- Option 6M.2 Mounted 8' aluminum platform body meeting Specification E1320SRW (Minimum 1" aluminum extruded floor instead of steel) EACH \$ \_\_\_\_\_  
MAKE \_\_\_\_\_ MODEL \_\_\_\_\_
- Option 6N. Permanently installed bulkhead to fit truck application (Minimum requirement to top of cab) EACH \$ \_\_\_\_\_
- Option 6O. Mounted standard utility tool body. EACH \$ \_\_\_\_\_

Acceptable makes and models are:

Knapheide 696J	Stahl CHALLENGER II 96VVS - 48.5
Reading Classic II 98A S.W.	RKI -L5680
Omaha 96V	RKI L5780 (for Dodge)

Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

- Option 6P. Utility tool body 3 section, tempered steel telescopic sliding roof and two-piece rigid aluminum endgate cover to protect cargo area from weather and theft EACH \$ \_\_\_\_\_
- Option 6Q. Heavy duty, Class V (2-1/2" square tube) receiver trailer hitch. Includes an adapter to reduce to 2" (Class III/IV) and a seven-wire RV style trailer plug (needed if ordering bed delete, Option 6K) EACH \$ \_\_\_\_\_

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_

Delivery will be made approximately \_\_\_\_\_ days after receipt of order.

**ITEM # 7 - New standard equipped 2014 or Newer Model 2WD Regular Cab 1 Ton Pickup with Dual Rear Wheels.**

**ACCEPTABLE MAKES AND MODELS:**

Standard Ford F-350 with 137" Wheelbase, Cab to Axle 56"

Standard Chevrolet 3500 with 133" Wheelbase, Cab to Axle 56"

Standard Dodge 3500 with 140" Wheelbase, Cab to Axle 56"

**\*This item number is not recommended for a plow\***

**All units bid must contain the following options:**

1. Standard, minimum V8 fuel-injected gasoline engine (Size \_\_\_\_\_ Horsepower \_\_\_\_\_)
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds \_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(4) manufacturer's standard all season, plus full size spare and wheel (Size \_\_\_\_\_)
7. Minimum 11,000 lbs. GVWR
8. Heavy-duty (Type III) trailer package to include receiver hitch
9. 8' Bed
10. Brakes, 4-wheel anti-lock braking system (ABS)
11. Speed control and tilt wheel
12. Rubber Flooring
13. Vinyl seats
14. 3 sets of keys

**DEALER COMPLETE:**

2014 MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_

FUEL CAPACITY \_\_\_\_\_ FUEL CAPACITY (2) \_\_\_\_\_ OIL CAPACITY \_\_\_\_\_

IS THIS ENGINE E-85 COMPATIBLE? \_\_\_\_\_ IF SO WHAT IS E-85 MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_

BUMPER TO BUMPER WARRANTY \_\_\_\_\_

POWERTRAIN WARRANTY \_\_\_\_\_

EXTENDED WARRANTY \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 7**

Indicate the additional cost or deduction for the below listed options, which should include all required options and special equipment.

Option 7A. Heavy-duty manual transmission in lieu of automatic transmission EACH \$ \_\_\_\_\_

Option 7B. Exterior color to be Federal Standard #595B "Highway Yellow" EACH \$ \_\_\_\_\_

Option 7C. Standard diesel engine in lieu of gasoline engine EACH \$ \_\_\_\_\_  
(State size and horsepower)

SIZE \_\_\_\_\_ HORSEPOWER \_\_\_\_\_

Option 7D. CNG engine in lieu of gasoline engine (provide the following information) EACH \$ \_\_\_\_\_

ENGINE: SIZE \_\_\_\_\_ HP \_\_\_\_\_ MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

TRANSMISSION: MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

CNG TANK: DGE CAPACITY \_\_\_\_\_ TANK LOCATION \_\_\_\_\_



**ITEM # 8 - New standard equipped 2014 or Newer Model 4WD Regular Cab 1 Ton Pickup with Dual Rear Wheels.**

**ACCEPTABLE MAKES AND MODELS:**

Standard Ford F-350 with 137" Wheelbase, Cab to Axle 56"

Standard Chevrolet 3500 with 133" Wheelbase, Cab to Axle 56"

Standard Dodge 3500 with 140" Wheelbase, Cab to Axle 56"

**All units bid must contain the following options:**

1. Standard, minimum V8 fuel-injected gasoline engine (Size\_\_\_\_\_ Horsepower\_\_\_\_\_)
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds\_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(4) manufacturer's standard all season, plus full size spare and wheel (Size\_\_\_\_\_)
7. Minimum 11,000 lbs. GVWR
8. Heavy-duty (Type III) trailer package to include receiver hitch
9. 8' Bed
10. Brakes, 4-wheel anti-lock braking system (ABS)
11. Speed control and tilt wheel
12. Rubber Flooring
13. Vinyl seats
14. 3 sets of keys

**DEALER COMPLETE:**

2014 MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_

FUEL CAPACITY \_\_\_\_\_ FUEL CAPACITY (2) \_\_\_\_\_ OIL CAPACITY \_\_\_\_\_

IS THIS ENGINE E-85 COMPATIBLE? \_\_\_\_\_ IF SO WHAT IS E-85 MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_

BUMPER TO BUMPER WARRANTY \_\_\_\_\_

POWERTRAIN WARRANTY \_\_\_\_\_

EXTENDED WARRANTY \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 8**

Indicate the additional cost or deduction for the below listed options, which should include all required options and special equipment.

Option 8A. Heavy-duty manual transmission in lieu of automatic transmission EACH \$ \_\_\_\_\_

Option 8B. Exterior color to be Federal Standard #595B "Highway Yellow" EACH \$ \_\_\_\_\_

Option 8C. Standard diesel engine in lieu of gasoline engine EACH \$ \_\_\_\_\_  
(state size and horsepower)

SIZE \_\_\_\_\_ HORSEPOWER \_\_\_\_\_

Option 8D. CNG engine in lieu of gasoline engine (provide the following information) EACH \$ \_\_\_\_\_

ENGINE: SIZE \_\_\_\_\_ HP \_\_\_\_\_ MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

TRANSMISSION: MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

CNG TANK: DGE CAPACITY \_\_\_\_\_ TANK LOCATION \_\_\_\_\_



**ITEM # 9 - New standard equipped 2014 or Newer Model 1 Ton 2WD Regular Chassis-Cab with DRW and 60" CA**

**ACCEPTABLE MAKES AND MODELS:**

Standard Ford F-350 with 141" Wheelbase Cab Axle 60"

Standard Chevrolet 3500HD/GMC 3500HD 137" Wheelbase Cab Axle 60"

Standard Dodge 3500 143" Wheelbase Cab Axle 60"

**\*This item number is not recommended for a plow\***

**All units bid must contain the following options:**

1. Standard, diesel engine with the highest cooling capacity Size \_\_\_\_\_ Horsepower \_\_\_\_\_)
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic transmission (Speeds \_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(4) manufacturer's standard all season, plus full size spare and wheel (Size \_\_\_\_\_)
7. Minimum GVWR 11,000 lb
8. Brakes, 4-wheel anti-lock braking system (ABS)
9. Speed control and tilt wheel
10. Rubber flooring
11. Back up alarm
12. Vinyl seats
13. 3 sets of keys

**DEALER COMPLETE IN DETAIL:**

2014 MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_

FUEL CAPACITY \_\_\_\_\_ FUEL CAPACITY (2) \_\_\_\_\_ OIL CAPACITY \_\_\_\_\_

BUMPER TO BUMPER WARRANTY \_\_\_\_\_

POWERTRAIN WARRANTY \_\_\_\_\_

EXTENDED WARRANTY \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 9**

Indicate the additional cost or deduction for the below listed options. Price should include all required options and special equipment.

Option 9A.1 Mounted 9' platform body meeting Specification E1320DRW EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 9A.2 Mounted aluminum 9' platform body meeting Specification E1320DRW  
(Minimum 1 1/4" aluminum extruded floor instead of steel) EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 9B.1 Mounted 9' platform dump body meeting Specification E1327 EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 9B.2 Mounted aluminum 9' platform dump body meeting Specification E1327  
(Minimum 1 1/4" aluminum extruded floor instead of steel) EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

- Option 9C.1 Mounted 9' dump body meeting Specification E1335 EACH \$ \_\_\_\_\_  
 MAKE \_\_\_\_\_ MODEL \_\_\_\_\_
- Option 9C.2 Mounted 9' aluminum dump body meeting Specification E1335-ALUM EACH \$ \_\_\_\_\_  
 MAKE \_\_\_\_\_ MODEL \_\_\_\_\_
- Option 9D. Permanently installed bulkhead to fit truck application EACH \$ \_\_\_\_\_  
 (Minimum requirement to top of cab)
- Option 9E. Provide live hydraulics with under hood clutch pump. Pump shall be cast iron EACH \$ \_\_\_\_\_  
 design capable of 3500 PSI; aluminum pumps will not be accepted. Reservoir shall  
 be 7 gallon with filtered breather cap, suction strainer, sight gauge and in tank  
 return filter rated to 25 GPM. Valve shall be cable operated. Control valve must  
 have a main relief and a relief for the hoist down function.  
 This shall control the hoist only.
- Option 9F. Provide hydraulics and controls 12VDC activated for dump hoist only EACH \$ \_\_\_\_\_
- Option 9G. Mounted standard utility tool body EACH \$ \_\_\_\_\_

Acceptable makes and models are:

Knapheide 6108D54J,                      Stahl CHALLENGER II 108VVD- 54,  
 Reading CLASSIC II 108A D.W.        RKI L60DW94.  
 Omaha 108D54V,

Body to include flush mounted LED tail, stop, turn, backup and clearance lights  
 as required per FMVSS 108 standards. Unit must include a tread plate step  
 bumper with pintle hook recess.

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

- Option 9H. Six - 2" deep full width 250 lb. capacity, free-sliding tool drawers mounted EACH \$ \_\_\_\_\_  
 approximately 1 ½" from top of compartment with approximately 2 ½"  
 between trays in lieu of two shelves and dividers in one of the full height  
 vertical compartment.
- Option 9I. Two full length 250 lbs. capacity free sliding tool trays with metal dividers EACH \$ \_\_\_\_\_  
 with slots on 4" centers with first tray mounted 5 ¼" from bottom of  
 compartment with approximately 1 ½" between trays with second tray  
 mounted above first in lieu of shelf and dividers in one of the horizontal  
 compartments.
- Option 9J. Flip top for Utility Body: Top of compartment opens for storage. EACH \$ \_\_\_\_\_  
 Can be either side or both sides. Telescopic roof and crane mounting kit  
 will impact flip top application. Latch is located in center horizontal  
 compartment.
- Option 9K. One - double bottle gas drop well and retainers in lieu of three shelves EACH \$ \_\_\_\_\_  
 and dividers in one of the full height vertical compartments, maintaining  
 an interior height of 48".
- Option 9L. Minimum 25" high panel extension cover with minimum 42" locking rear EACH \$ \_\_\_\_\_  
 doors which will provide a minimum 48" interior height for storage and  
 work area (Canopy Roof Style).
- Option 9M. Body to have 3 section, tempered steel telescopic sliding roof and two piece, EACH \$ \_\_\_\_\_  
 rigid aluminum, end gate cover to protect cargo area from weather and theft.  
 A mechanical type seal will be placed on the telescopic sliding roof and end  
 gate cover.

- Option 9N. Raise Telescopic Roof to get 36" clearance for the above option. EACH \$ \_\_\_\_\_
- Option 9O. Crane mount reinforced rigidly while maintaining full compartment space on top rear corner of body either left or right for a 3500 lbs. capacity crane (with no mounting holes or bolt holes, we will drill to suit ourselves) EACH \$ \_\_\_\_\_
- Option 9P. Commercial grade spray on bed lining to be applied in the cargo area of the utility body, to include floor, sides tailgate, front, and horizontal surface of bumper EACH \$ \_\_\_\_\_
- Option 9Q. Heavy-duty 5 or 6 speed manual transmission in lieu of automatic transmission EACH \$ \_\_\_\_\_
- Option 9R. Heavy - duty, Class V (2-1/2 " square tube) receiver trailer hitch. Includes an adapter to reduce to 2" (Class III/IV) and a seven-wire RV style trailer plug EACH \$ \_\_\_\_\_
- Option 9S. Exterior color to be Federal Standard #595B "Highway Yellow" EACH \$ \_\_\_\_\_
- Option 9T. Standard gasoline engine in lieu of diesel engine with the highest cooling capacity (State size and horsepower) EACH \$ \_\_\_\_\_  
 SIZE \_\_\_\_\_ HORSEPOWER \_\_\_\_\_
- Option 9U. CNG engine in lieu of gasoline engine (provide the following information) EACH \$ \_\_\_\_\_  
 ENGINE: SIZE \_\_\_\_\_ HP \_\_\_\_\_ MAKE \_\_\_\_\_ MODEL \_\_\_\_\_  
 TRANSMISSION: MAKE \_\_\_\_\_ MODEL \_\_\_\_\_  
 CNG TANK: DGE CAPACITY \_\_\_\_\_ TANK LOCATION \_\_\_\_\_
- Option 9V. Automatic transmission power take-off provision EACH \$ \_\_\_\_\_
- Option 9W. 2 Full length cab steps or running boards. (One on drivers side, one on passenger side.) SET \$ \_\_\_\_\_
- Option 9X. Optional Rear Axle Ratio Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 9Y. Limited Slip Rear Axle Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 9Z. Electric Trailer Brake Controller EACH \$ \_\_\_\_\_
- Option 9AA. Bluetooth Capability EACH \$ \_\_\_\_\_

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_

Delivery will be made approximately \_\_\_\_\_ days after receipt of order.

**ITEM # 10 - New standard equipped 2014 or Newer Model 1 Ton 4WD Regular Chassis-Cab with DRW and 60" CA**

**ACCEPTABLE MAKES AND MODELS:**

Standard Ford F-350 with 141" Wheelbase Cab Axle 60"  
Standard Chevrolet 3500HD/GMC 3500HD 137" Wheelbase Cab Axle 60"  
Standard Dodge 3500 143" Wheelbase Cab Axle 60"

**All units bid must contain the following options:**

1. Standard, diesel engine with the highest cooling capacity Size \_\_\_\_\_ Horsepower \_\_\_\_\_ )
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic transmission (Speeds \_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires: (4) manufacturer's standard all season, plus full size spare and wheel (Size \_\_\_\_\_)
7. Minimum GVWR 11,000 lb
8. Brakes, 4-wheel anti-lock braking system (ABS)
9. Speed control and tilt wheel
10. Rubber flooring
11. Back up alarm
12. Vinyl seats
13. 3 sets of keys

**DEALER COMPLETE IN DETAIL:**

2014 MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_

FUEL CAPACITY \_\_\_\_\_ FUEL CAPACITY (2) \_\_\_\_\_ OIL CAPACITY \_\_\_\_\_

BUMPER TO BUMPER WARRANTY \_\_\_\_\_

POWERTRAIN WARRANTY \_\_\_\_\_

EXTENDED WARRANTY \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 10**

Indicate the additional cost or deduction for the below listed options. Price should include all required options and special equipment.

Option 10A.1 Mounted 9' platform body meeting Specification E1320DRW EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 10A.2 Mounted 9' aluminum platform body meeting Specification E1320DRW EACH \$ \_\_\_\_\_  
(Minimum 1 1/4" aluminum extruded floor instead of steel)

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 10B.1 Mounted 9' platform dump body meeting Specification E1327 EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 10B.2 Mounted 9' aluminum platform dump body meeting Specification E1327 EACH \$ \_\_\_\_\_  
(Minimum 1 1/4" aluminum extruded floor instead of steel)

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

- Option 10C.1** Mounted 9' dump body meeting Specification E1335 EACH \$ \_\_\_\_\_  
**MAKE** \_\_\_\_\_ **MODEL** \_\_\_\_\_
- Option 10C.2** Mounted 9' aluminum dump body meeting Specification E1335-ALUM EACH \$ \_\_\_\_\_  
**MAKE** \_\_\_\_\_ **MODEL** \_\_\_\_\_
- Option 10D.** Permanently installed bulkhead to fit truck application (minimum requirement to top of cab) EACH \$ \_\_\_\_\_
- Option 10E.** Provide live hydraulics with under hood clutch pump. Pump shall be cast iron design capable of 3500 PSI; aluminum pumps will not be accepted. Reservoir shall be 15 gallon with filtered breather cap, suction strainer, sight gauge and in tank return filter rated to 25 GPM. Control valve shall be 3 section mobile stack valve for hoist, plow and spreader. Valve shall be 12VDC activated capable of a minimum 12 GPM and installed in a valve enclosure. Control valve must have a main relief and a relief for the hoist down function. The hoist, plow and spreader functions shall be controlled by a Certified Power Freedom 2.0 12VDC control console with automated spreading for mounted dump body in specification E1335 or mounted platform body in specification E1327. This package shall be capable of driving the auger, spinner motor in a salt spreader, and power to raise angle plow. All hoses shall be provided from front to rear of truck. EACH \$ \_\_\_\_\_
- Option 10F.** Hydraulic system to run body, plow and spreader, hoist and plow controls to be manual cable controlled and the spreader control shall be a Certified Power Freedom 2.0 automated spreader control. The hydraulic system requirements shall match the 10E specifications. EACH \$ \_\_\_\_\_
- Option 10G.** Provide hydraulics and controls 12VDC activated for dump hoist only EACH \$ \_\_\_\_\_
- Option 10H.** Mounted standard utility tool body EACH \$ \_\_\_\_\_  
Acceptable makes and models are:  
Knapheide 6108D54J, Stahl CHALLENGER II 108VVD- 54,  
Reading CLASSIC II 108A D.W. RKI L60DW94.  
Omaha 108D54V,  
Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess  
**MAKE** \_\_\_\_\_ **MODEL** \_\_\_\_\_
- Option 10I.** Six - 2" deep full width 250 lb. capacity, free-sliding tool drawers mounted approximately 1 ½" from top of compartment with approximately 2 ½" between trays in lieu of two shelves and dividers in one of the full height vertical compartment EACH \$ \_\_\_\_\_
- Option 10J.** Two full length 250 lbs. capacity free sliding tool trays with metal dividers with slots on 4" centers with first tray mounted 5 ¼" from bottom of compartment with approximately 1 ½" between trays with second tray mounted above first in lieu of shelf and dividers in one of the horizontal compartments EACH \$ \_\_\_\_\_
- Option 10K.** Flip top for Utility Body: Top of compartment opens for storage. Can be either side or both sides. Telescopic roof and crane mounting kit will impact flip top application. Latch is located in center horizontal compartment. EACH \$ \_\_\_\_\_
- Option 10L.** One - double bottle gas drop well and retainers in lieu of three shelves and dividers in one of the full height vertical compartments, maintaining an interior height of 48" EACH \$ \_\_\_\_\_

- Option 10M. Minimum 25" high panel extension cover with minimum 42" locking rear doors which will provide a minimum 48" interior height for storage and work area (Canopy roof style). EACH \$ \_\_\_\_\_
- Option 10N. Body to have 3 section, tempered steel telescopic sliding roof and two piece, rigid aluminum, end gate cover to protect cargo area from weather and theft. A mechanical type seal will be placed on the telescopic sliding roof and end gate cover EACH \$ \_\_\_\_\_
- Option 10O. Raise Telescopic Roof to get 36" clearance for the above option EACH \$ \_\_\_\_\_
- Option 10P. Crane mount reinforced rigidly while maintaining full compartment space on top rear corner of body either left or right for a 3500 lbs. capacity crane (with no mounting holes or bolt holes, we will drill to suit ourselves) EACH \$ \_\_\_\_\_
- Option 10Q. Commercial grade spray on bed lining to be applied in the cargo area of the utility body, to include floor, sides tailgate, front, and horizontal surface of bumper EACH \$ \_\_\_\_\_
- Option 10R. Heavy-duty 5 or 6 speed manual transmission in lieu of automatic transmission EACH \$ \_\_\_\_\_
- Option 10S. Heavy - duty, Class V (2-1/2 " square tube) receiver trailer hitch. Includes an adapter to reduce to 2" (Class III/IV) and a seven-wire RV style trailer plug EACH \$ \_\_\_\_\_
- Option 10T. Exterior color to be Federal Standard #595B "Highway Yellow" EACH \$ \_\_\_\_\_
- Option 10U. Standard gasoline engine in lieu of diesel engine with the highest cooling capacity (State size and horsepower) EACH \$ \_\_\_\_\_  
 SIZE \_\_\_\_\_ HORSEPOWER \_\_\_\_\_
- Option 10V. CNG engine in lieu of gasoline engine (provide the following information) EACH \$ \_\_\_\_\_  
 ENGINE: SIZE \_\_\_\_\_ HP \_\_\_\_\_ MAKE \_\_\_\_\_ MODEL \_\_\_\_\_  
 TRANSMISSION: MAKE \_\_\_\_\_ MODEL \_\_\_\_\_  
 CNG TANK: DGE CAPACITY \_\_\_\_\_ TANK LOCATION \_\_\_\_\_
- Option 10W. Snow plow package EACH \$ \_\_\_\_\_
- Option 10X. Automatic transmission power take-off provision EACH \$ \_\_\_\_\_
- Option 10Y. 2 Full length cab steps or running boards. SET \$ \_\_\_\_\_  
 (One on drivers side, one on passenger side.)
- Option 10Z. Optional Rear Axle Ratio Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 10AA. Limited Slip Rear Axle Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 10BB. Electric Trailer Brake Controller EACH \$ \_\_\_\_\_
- Option 10CC. Bluetooth Capability EACH \$ \_\_\_\_\_

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_

Delivery will be made approximately \_\_\_\_\_ days after receipt of order.

**ITEM # 11 - New standard equipped 2014 or Newer Model 1 Ton 2WD Regular Chassis-Cab with DRW and 84" CA**

**ACCEPTABLE MAKES AND MODELS:**

Standard Ford F-350 with 165" Wheelbase Cab to Axle 84"

Standard Chevrolet 3500 HD/GMC 3500 HD with 161" Wheelbase Cab to Axle 84"

Standard Dodge Ram 3500 with 167 Cab to Axle 84"

**\*This item number is not recommended for a plow\***

**All units bid must contain the following options:**

1. Standard, diesel engine with the highest cooling capacity (Size \_\_\_\_\_ Horsepower \_\_\_\_\_)
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic transmission (Speeds \_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(4) manufacturer's standard all season, plus full size spare and wheel (Size \_\_\_\_\_)
7. Minimum GVWR 11,000
8. Brakes 4-wheel anti-lock braking system (ABS)
9. Speed control and tilt wheel
10. Rubber flooring
11. Back up alarm
12. Vinyl seats
13. 3 sets of keys

**DEALER COMPLETE IN DETAIL:**

2014 MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_

FUEL CAPACITY \_\_\_\_\_ FUEL CAPACITY (2) \_\_\_\_\_ OIL CAPACITY \_\_\_\_\_

BUMPER TO BUMPER WARRANTY \_\_\_\_\_

POWERTRAIN WARRANTY \_\_\_\_\_

EXTENDED WARRANTY \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 11**

Indicate the additional cost or deduction for the below listed options. Prices should include all required options and special equipment.

Option 11A.1 Mounted 11' platform body meeting Specification E1320DRW EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 11A.2 Mounted 11' aluminum platform body meeting Specification E1320DRW  
(Minimum 1 1/4" aluminum extruded floor instead of steel) EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 11B.1 Mounted 11' platform dump body meeting Specification E1327 EACH \$ \_\_\_\_\_

(MAKE) \_\_\_\_\_ (MODEL) \_\_\_\_\_

Option 11B.2 Mounted 11' aluminum platform dump body meeting Specification E1327  
(Minimum 1 1/4" aluminum extruded floor instead of steel) EACH \$ \_\_\_\_\_

(MAKE) \_\_\_\_\_ (MODEL) \_\_\_\_\_

- Option 11C. Permanently installed bulkhead to fit truck application (Minimum requirement to top of cab) EACH \$ \_\_\_\_\_
- Option 11D. Provide live hydraulics with under hood clutch pump. Pump shall be cast iron design capable of 3500 PSI; aluminum pumps will not be accepted. Reservoir shall be 7 gallon with filtered breather cap, suction strainer, sight gauge and in tank return filter rated to 25 GPM. Valve shall be cable operated. Control valve must have a main relief and a relief for the hoist down function. This shall control the hoist only. EACH \$ \_\_\_\_\_
- Option 11E. Provide hydraulics and controls 12VDC activated for dump hoist only EACH \$ \_\_\_\_\_
- Option 11F. Mounted standard utility tool body EACH \$ \_\_\_\_\_
- Acceptable makes and models are:
- |                            |                            |
|----------------------------|----------------------------|
| Knapheide 6132D54J         | Stahl CHALLENGER 132VVD-54 |
| Reading CLASSIC II 132A DW | RKI L84DW94                |
| Omaha 132D54V              |                            |
- Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess
- (MAKE) \_\_\_\_\_ (MODEL) \_\_\_\_\_
- Option 11G. Six - 2” deep full width 250 lbs. capacity free sliding tool drawers mounted approximately 1 ½” from top of compartment with approximately 2 ½” between trays in lieu of two shelves and dividers in one of the full height vertical compartments EACH \$ \_\_\_\_\_
- Option 11H. Two full length 250 lbs. capacity free sliding tool trays with metal dividers with slots on 4” centers with first tray mounted 5 ¼ “ from bottom of compartment with approximately 1 ½” between trays with second tray mounted above first in lieu of shelf and dividers in one of the horizontal compartments EACH \$ \_\_\_\_\_
- Option 11I. Flip top for Utility Body: Top of compartment opens for storage. Can be either side or both sides. Telescopic roof and crane mounting kit will impact flip top application. Latch is located in center horizontal compartment. EACH \$ \_\_\_\_\_
- Option 11J. Minimum 25” high panel extension cover with minimum 42” locking rear doors which will provide a minimum 48” interior height for storage and work area (Canopy roof style). EACH \$ \_\_\_\_\_
- Option 11K. Body to have 3 sections, tempered steel telescopic sliding roof and two-piece, rigid aluminum, end gate cover to protect cargo area from weather and theft. A mechanical type seal will be placed on the telescopic sliding roof and end gate cover EACH \$ \_\_\_\_\_
- Option 11L. Raise Telescopic Roof to get 36” clearance for the above option EACH \$ \_\_\_\_\_
- Option 11M. Crane mount reinforced rigidly while maintaining full compartment space on top rear corner of body either left or right for a 3500 lbs. capacity crane (with no mounting holes or boltholes, we will drill to suit ourselves) EACH \$ \_\_\_\_\_
- Option 11N. One - double bottle gas drop well with minimum 55” clearance height (for large Bottle use) and retainers in lieu of the interior 48” full height vertical compartment EACH \$ \_\_\_\_\_

- Option 11O. Commercial grade spray on bed lining to be applied in the cargo area of the utility body, to include floor, sides tailgate, front, and horizontal surface of bumper EACH \$ \_\_\_\_\_
- Option 11P. Heavy-duty manual 5 or 6 speed transmission in lieu of automatic transmission EACH \$ \_\_\_\_\_
- Option 11Q. Heavy duty, Class V (2-1/2" square tube) receiver trailer hitch. Includes an adapter to reduce to 2" (Class III/IV) and a seven-wire RV style trailer plug EACH \$ \_\_\_\_\_
- Option 11R. Exterior color to be Federal Standard #595B "Highway Yellow" EACH \$ \_\_\_\_\_
- Option 11S. Standard gasoline engine with the highest cooling capacity in lieu of diesel engine (State size and horsepower) EACH \$ \_\_\_\_\_  
 SIZE \_\_\_\_\_ HORSEPOWER \_\_\_\_\_
- Option 11T. CNG engine in lieu of gasoline engine (provide the following information) EACH \$ \_\_\_\_\_  
 ENGINE: SIZE \_\_\_\_\_ HP \_\_\_\_\_ MAKE \_\_\_\_\_ MODEL \_\_\_\_\_  
 TRANSMISSION: MAKE \_\_\_\_\_ MODEL \_\_\_\_\_  
 CNG TANK: DGE CAPACITY \_\_\_\_\_ TANK LOCATION \_\_\_\_\_
- Option 11U. Automatic transmission power take off provision EACH \$ \_\_\_\_\_
- Option 11V. 2 Full-length cab steps or running boards. (One on drivers side, one on passenger side) SET \$ \_\_\_\_\_
- Option 11W. Optional Rear Axle Ratio Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 11X. Limited Slip Rear Axle Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 11Y. Electric Trailer Brake Controller EACH \$ \_\_\_\_\_
- Option 11Z. Bluetooth Capability EACH \$ \_\_\_\_\_

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_

Delivery will be made approximately \_\_\_\_\_ days after receipt of order.

**ITEM # 12 - New standard equipped 2014 or Newer Model 1 Ton 4WD Regular Chassis-Cab with DRW and 84" CA**

**ACCEPTABLE MAKES AND MODELS:**

Standard Ford F-350 with 165" Wheelbase Cab to Axle 84"

Standard Chevrolet 3500 HD/GMC 3500 HD with 161" Wheelbase Cab to Axle 84"

Standard Dodge Ram 3500 with 167 Cab to Axle 84"

**All units bid must contain the following options:**

1. Standard, diesel engine with the highest cooling capacity (Size \_\_\_\_\_) Horsepower \_\_\_\_\_)
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic transmission (Speeds \_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(4) manufacturer's standard all season, plus full size spare and wheel (Size \_\_\_\_\_)
7. Minimum GVWR 11,000
8. Brakes 4-wheel anti-lock braking system (ABS)
9. Speed control and tilt wheel
10. Rubber flooring
11. Back up alarm
12. Vinyl seats
13. 3 sets of keys

**DEALER COMPLETE IN DETAIL:**

2014 MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_

FUEL CAPACITY \_\_\_\_\_ FUEL CAPACITY (2) \_\_\_\_\_ OIL CAPACITY \_\_\_\_\_

BUMPER TO BUMPER WARRANTY \_\_\_\_\_

POWERTRAIN WARRANTY \_\_\_\_\_

EXTENDED WARRANTY \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 12**

Indicate the additional cost or deduction for the below listed options. Prices should include all required options and special equipment.

Option 12A.1 Mounted 11' platform body meeting Specification E1320DRW EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 12A.2 Mounted 11' aluminum platform body meeting Specification E1320DRW (Minimum 1 1/4" aluminum extruded floor instead of steel) EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 12B.1 Mounted 11' platform dump body meeting Specification E1327 EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 12B.2 Mounted 11' aluminum platform dump body meeting Specification E1327 (Minimum 1 1/4" aluminum extruded floor instead of steel) EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 12C. Permanently installed bulkhead to fit truck application (Minimum requirement to top of cab) EACH \$ \_\_\_\_\_

- Option 12D.** Provide live hydraulics with under hood clutch pump. Pump shall be cast iron design capable of 3500 PSI; aluminum pumps will not be accepted. Reservoir shall be 15 gallon with filtered breather cap, suction strainer, sight gauge and in tank return filter rated to 25 GPM. Control valve shall be 3 section mobile stack valve for hoist, plow and spreader. Valve shall be 12VDC activated capable of a minimum 12 GPM and installed in a valve enclosure. Control valve must have a main relief and a relief for the hoist down function. The hoist, plow and spreader functions shall be controlled by a Certified Power Freedom 2.0 12VDC control console with automated spreading for mounted dump body in specification E1335 or mounted platform body in specification E1327. This package shall be capable of driving the auger, spinner motor in a salt spreader, and power to raise angle plow. All hoses shall be provided from front to rear of truck. EACH \$ \_\_\_\_\_
- Option 12E.** Hydraulic system to run body, plow and spreader, hoist and plow controls to be manual cable controlled and the spreader control shall be a Certified Power Freedom 2.0 automated spreader control. The hydraulic system requirements shall match the 12D specifications. EACH \$ \_\_\_\_\_
- Option 12F.** Provide hydraulics and controls 12VDC activated for dump hoist only EACH \$ \_\_\_\_\_
- Option 12G.** Mounted standard utility tool body EACH \$ \_\_\_\_\_
- Acceptable makes and models are:
- |                            |                            |
|----------------------------|----------------------------|
| Knapheide 6132D54J         | Stahl CHALLENGER 132VVD-54 |
| Reading CLASSIC II 132A DW | RKI L84DW94                |
| Omaha 132D54V              |                            |
- Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess.
- MAKE \_\_\_\_\_ MODEL \_\_\_\_\_
- Option 12H.** Six - 2” deep full width 250 lbs. capacity free sliding tool drawers mounted approximately 1 ½” from top of compartment with approximately 2 ½” between trays in lieu of two shelves and dividers in one of the full height vertical compartments EACH \$ \_\_\_\_\_
- Option 12I.** Two full length 250 lbs. capacity free sliding tool trays with metal dividers with slots on 4” centers with first tray mounted 5 ¼ “ from bottom of compartment with approximately 1 ½” between trays with second tray mounted above first in lieu of shelf and dividers in one of the horizontal compartments EACH \$ \_\_\_\_\_
- Option 12J.** Flip top for Utility Body: Top of compartment opens for storage. Can be either side or both sides. Telescopic roof and crane mounting kit will impact flip top application. Latch is located in center horizontal compartment. EACH \$ \_\_\_\_\_
- Option 12K.** Minimum 25” high panel extension cover with minimum 42” locking rear doors which will provide a minimum 48” interior height for storage and work area (Canopy roof style). EACH \$ \_\_\_\_\_
- Option 12L.** Body to have 3 sections, tempered steel telescopic sliding roof and two-piece, rigid aluminum, end gate cover to protect cargo area from weather and theft. A mechanical type seal will be placed on the telescopic sliding roof and end gate cover EACH \$ \_\_\_\_\_
- Option 12M.** Raise Telescopic Roof to get 36” clearance for the above option EACH \$ \_\_\_\_\_

- Option 12N. Crane mount reinforced rigidly while maintaining full compartment space on top rear corner of body either left or right for a 3500 lbs. capacity crane (with no mounting holes or bolt holes, we will drill to suit ourselves) EACH \$ \_\_\_\_\_
- Option 12O. One - double bottle gas drop well with minimum 55" clearance height (for large bottle use) and retainers in lieu of the interior 48" full height vertical compartment EACH \$ \_\_\_\_\_
- Option 12P. Commercial grade spray on bed lining to be applied in the cargo area of the utility body, to include floor, sides tailgate, front, and horizontal surface of bumper EACH \$ \_\_\_\_\_
- Option 12Q. Heavy-duty manual 5 or 6 speed transmission in lieu of automatic transmission EACH \$ \_\_\_\_\_
- Option 12R. Heavy duty, Class V (2-1/2 " square tube) receiver trailer hitch. Includes an adapter to reduce to 2" (Class III/IV) and a seven-wire RV style trailer plug EACH \$ \_\_\_\_\_
- Option 12S. Exterior color to be Federal Standard #595B "Highway Yellow" EACH \$ \_\_\_\_\_
- Option 12T. Standard gasoline engine with the highest cooling capacity in lieu of diesel engine (State size and horsepower) EACH \$ \_\_\_\_\_  
 SIZE \_\_\_\_\_ HORSEPOWER \_\_\_\_\_
- Option 12U. CNG engine in lieu of gasoline engine (provide the following information) EACH \$ \_\_\_\_\_  
 ENGINE: SIZE \_\_\_\_\_ HP \_\_\_\_\_ MAKE \_\_\_\_\_ MODEL \_\_\_\_\_  
 TRANSMISSION: MAKE \_\_\_\_\_ MODEL \_\_\_\_\_  
 CNG TANK: DGE CAPACITY \_\_\_\_\_ TANK LOCATION \_\_\_\_\_
- Option 12V. Snowplow package EACH \$ \_\_\_\_\_
- Option 12W. Automatic transmission power take off provision EACH \$ \_\_\_\_\_
- Option 12X. 2 Full-length cab steps or running boards. (One on drivers side, one on passenger side) SET \$ \_\_\_\_\_
- Option 12Y. Optional Rear Axle Ratio Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 12Z. Limited Slip Rear Axle Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 12AA. Electric Trailer Brake Controller EACH \$ \_\_\_\_\_
- Option 12BB. Bluetooth Capability EACH \$ \_\_\_\_\_

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

*% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_*

Delivery will be made approximately \_\_\_\_\_ days after receipt of order.

**ITEM # 13 - New standard equipped 2014 or Newer Model 15,000 LB. GVWR Chassis-Cab with DRW and 60" CA.**

**ACCEPTABLE MAKES AND MODELS:**

Standard Ford Super Duty F450 with 141" Wheelbase Cab to Axle 60"

Standard Dodge 4500 with 144.3" Wheelbase, Cab to Axle 60.2"

**All units bid must contain the following options:**

1. Standard, diesel engine with the highest cooling capacity (Size \_\_\_\_\_ Horsepower \_\_\_\_\_)
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds \_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(4) manufacturer's standard all season, plus full size spare and wheel (Size \_\_\_\_\_)
7. Rubber flooring
8. Minimum GVWR 15,000 LB
9. Brakes 4-wheel anti-lock braking system (ABS)
10. Speed control and tilt wheel
11. Back up alarm
12. Vinyl seats
13. 3 sets of keys

**DEALER COMPLETE IN DETAIL**

2014 MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_

FUEL CAPACITY \_\_\_\_\_ FUEL CAPACITY (2) \_\_\_\_\_ OIL CAPACITY \_\_\_\_\_

BUMPER TO BUMPER WARRANTY \_\_\_\_\_

POWERTRAIN WARRANTY \_\_\_\_\_

EXTENDED WARRANTY \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 13**

Indicate the additional cost or deduction for the below listed options, which should include all required options and special equipment.

Option 13A.1 Mounted 9' platform body meeting Specification E1320DRW EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 13A.2 Mounted 9' aluminum platform body meeting Specification E1320DRW  
(Minimum 1 1/4" aluminum extruded floor instead of steel) EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 13B.1 Mounted 9' platform dump body meeting Specification E1327 EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 13B.2 Mounted 9' aluminum platform dump body meeting Specification E1327  
(Minimum 1 1/4" aluminum extruded floor instead of steel) EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 13C.1 Mounted 9' dump body meeting Specification E1335 EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 13C.2 Mounted 9' aluminum dump body meeting Specification E1335-ALUM EACH \$ \_\_\_\_\_  
MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 13D. Permanently installed bulkhead to fit truck application (minimum requirement to top of cab) EACH \$ \_\_\_\_\_

Option 13E. Provide live hydraulics with under hood clutch pump. Pump shall be cast iron design capable of 3500 PSI; aluminum pumps will not be accepted. Reservoir shall be 15 gallon with filtered breather cap, suction strainer, sight gauge and in tank return filter rated to 25 GPM. Control valve shall be 3 section mobile stack valve for hoist, plow and spreader. Valve shall be 12VDC activated capable of a minimum 12 GPM and installed in a valve enclosure. Control valve must have a main relief and a relief for the hoist down function. The hoist, plow and spreader functions shall be controlled by a Certified Power Freedom 2.0 12VDC control console with automated spreading for mounted dump body in specification E1335 or mounted platform body in specification E1327. This package shall be capable of driving the auger, spinner motor in a salt spreader, and power to raise angle plow. All hoses shall be provided from front to rear of truck. EACH \$ \_\_\_\_\_

Option 13F. Hydraulic system to run body, plow and spreader, hoist and plow controls to be manual cable controlled and the spreader control shall be a Certified Power Freedom 2.0 automated spreader control. The hydraulic system requirements shall match the 13E specifications. EACH \$ \_\_\_\_\_

Option 13G. Provide hydraulics and controls 12VDC activated for dump hoist only EACH \$ \_\_\_\_\_

Option 13H. Mounted standard utility tool body. EACH \$ \_\_\_\_\_

Acceptable makes and models are:

Knapheide 6108D54J RKI L60DW94.  
Reading CLASSIC II 108A DW Stahl CHALLENGER II 108VVD-54  
Omaha 108D54V,

Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 13I. Six - 2" deep full width 250 lbs. capacity free sliding tool drawers mounted approximately 1 1/2" from top of compartment with approximately 2 1/2" between trays in lieu of two shelves and dividers in one of the full height vertical compartments EACH \$ \_\_\_\_\_

Option 13J. Two full length 250 lbs. capacity free sliding tool trays with metal dividers with slots on 4" centers with first tray mounted 5 1/4" from bottom of compartment with approximately 1 1/2" between trays with second tray mounted above first in lieu of shelf and dividers in one of the horizontal compartments EACH \$ \_\_\_\_\_

Option 13K. Flip top for Utility Body: Top of compartment opens for storage. Can be either side or both sides. Telescopic roof and crane mounting kit will impact flip top application. Latch is located in center horizontal compartment EACH \$ \_\_\_\_\_

Option 13L. One - double bottle gas drop well and retainers in lieu of two shelves and dividers in one of the full height vertical compartments, maintaining an interior height of 48" EACH \$ \_\_\_\_\_

- Option 13M. Minimum 25" high panel extension cover with minimum 42" locking rear doors which will provide a minimum 48" interior height for storage and work area (Canopy roof style). EACH \$ \_\_\_\_\_
- Option 13N. Body to have 3 section, tempered steel telescopic sliding roof and two piece, rigid aluminum, endgate cover to protect cargo area from weather and theft. A mechanical type seal will be placed on the telescopic sliding roof and end gate cover. EACH \$ \_\_\_\_\_
- Option 13O. Raise Telescopic Roof to get 36" clearance for the above option. EACH \$ \_\_\_\_\_
- Option 13P. Crane mount reinforced rigidly while maintaining full compartment space on top rear corner of body either left or right for a 3500 lbs. capacity crane (with no mounting holes or bolt holes, we will drill to suit ourselves). EACH \$ \_\_\_\_\_
- Option 13Q. Commercial grade spray on bed lining to be applied in the cargo area of the utility body, to include floor, sides tailgate, front, and horizontal surface of bumper. EACH \$ \_\_\_\_\_
- Option 13R. Heavy-duty 5 or 6 speed manual transmission in lieu of automatic transmission. EACH \$ \_\_\_\_\_
- Option 13S. Heavy duty, Class V (2-1/2 " square tube) receiver trailer hitch. Includes an adapter to reduce to 2" (Class III/IV) and a seven-wire RV style trailer plug. EACH \$ \_\_\_\_\_
- Option 13T. Exterior color to be Federal Standard #595B "Highway Yellow". EACH \$ \_\_\_\_\_
- Option 13U. Standard gasoline engine with the highest cooling capacity in lieu of diesel engine (State size and horsepower). EACH \$ \_\_\_\_\_
- SIZE \_\_\_\_\_ HORSEPOWER \_\_\_\_\_
- Option 13V. Automatic transmission power take-off provision. EACH \$ \_\_\_\_\_
- Option 13W. 2 Full length cab steps or running boards. (One on drivers side, one on passenger side). SET \$ \_\_\_\_\_
- Option 13X. Optional Rear Axle Ratio Axle Ratio \_\_\_\_\_. EACH \$ \_\_\_\_\_
- Option 13Y. Limited Slip Rear Axle Axle Ratio \_\_\_\_\_. EACH \$ \_\_\_\_\_
- Option 13Z. Electric Trailer Brake Controller. EACH \$ \_\_\_\_\_
- Option 13AA. 4WD in lieu of 2WD. EACH \$ \_\_\_\_\_
- Option 13BB. Bluetooth Capability. EACH \$ \_\_\_\_\_

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_

Delivery will be made approximately \_\_\_\_\_ days after receipt of order.

**ITEM # 14 - New standard equipped 2014 or Newer Model 15000 LB. GVWR Chassis-Cab with DRW and 84" CA.**

**ACCEPTABLE MAKES AND MODELS:**

Standard Ford Super Duty F450 with 165" Wheelbase, Cab to Axle 84"

Standard Dodge 4500 with 168.3" Wheelbase, Cab to Axle 84"

**All units bid must contain the following options:**

1. Standard diesel engine with the highest cooling capacity (Size \_\_\_\_\_ Horsepower \_\_\_\_\_)
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds \_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(4) manufacturer's standard all season, plus full size spare and wheel (Size \_\_\_\_\_)
7. Rubber flooring
8. Minimum GVWR 15,000 LB
9. Brakes 4-wheel anti-lock braking system (ABS)
10. Speed control and tilt wheel
11. Back up alarm
12. Vinyl seats
13. 3 sets of keys

**DEALER COMPLETE IN DETAIL:**

2014 MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_

FUEL CAPACITY \_\_\_\_\_ FUEL CAPACITY (2) \_\_\_\_\_ OIL CAPACITY \_\_\_\_\_

BUMPER TO BUMPER WARRANTY \_\_\_\_\_

POWERTRAIN WARRANTY \_\_\_\_\_

EXTENDED WARRANTY \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 14**

Indicate the additional cost or deduction for the below listed options, which should include all required options and special equipment.

Option 14A.1 Mounted 12' platform body meeting Specification E1320DRW EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 14A.2 Mounted 12' aluminum platform body meeting Specification E1320DRW (Minimum 1 1/4" aluminum extruded floor instead of steel) EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 14B.1 Mounted 11' platform dump body meeting Specification E1327 EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 14B.2 Mounted 11' aluminum platform dump body meeting Specification E1327 (Minimum 1 1/4" aluminum extruded floor instead of steel) EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 14C. Permanently installed bulkhead to fit truck application (minimum requirement to top of cab) EACH \$ \_\_\_\_\_

- Option 14D.** Provide live hydraulics with under hood clutch pump. Pump shall be cast iron design capable of 3500 PSI; aluminum pumps will not be accepted. Reservoir shall be 15 gallon with filtered breather cap, suction strainer, sight gauge and in tank return filter rated to 25 GPM. Control valve shall be 3 section mobile stack valve for hoist, plow and spreader. Valve shall be 12VDC activated capable of a minimum 12 GPM and installed in a valve enclosure. Control valve must have a main relief and a relief for the hoist down function. The hoist, plow and spreader functions shall be controlled by a Certified Power Freedom 2.0 12VDC control console with automated spreading for mounted dump body in specification E1335 or mounted platform body in specification E1327. This package shall be capable of driving the auger, spinner motor in a salt spreader, and power to raise angle plow. All hoses shall be provided from front to rear of truck. EACH \$ \_\_\_\_\_
- Option 14E.** Hydraulic system to run body, plow and spreader, hoist and plow controls to be manual cable controlled and the spreader control shall be a Certified Power Freedom 2.0 automated spreader control. The hydraulic system requirements shall match the 14D specifications. EACH \$ \_\_\_\_\_
- Option 14F.** Provide hydraulics and controls 12VDC activated for dump hoist only EACH \$ \_\_\_\_\_
- Option 14G.** Mounted standard utility tool body. EACH \$ \_\_\_\_\_  
Acceptable makes and models are:  
Knapheide 6132D54J ,                      Stahl CHALLENGER II 132VVD-54  
Reading CLASSIC II 132A DW   Omaha 132D54V  
RKI L84DW94  
Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess.  
MAKE \_\_\_\_\_                      MODEL \_\_\_\_\_
- Option 14H.** Six - 2” deep full width 250 lbs. capacity free sliding tool drawers mounted approximately 1 ½” from top of compartment with approximately 2 ½” between trays in lieu of two shelves and dividers in one of the full height vertical compartments EACH \$ \_\_\_\_\_
- Option 14I.** Two full length 250 lbs. capacity free sliding tool trays with metal dividers with slots on 4” centers with first tray mounted 5 ¼ “ from bottom of compartment with approximately 1 ½” between trays with second tray mounted above first in lieu of shelf and dividers in one of the horizontal compartments EACH \$ \_\_\_\_\_
- Option 14J.** Flip top for Utility Body: Top of compartment opens for storage. Can be either side or both sides. Telescopic roof and crane mounting kit will impact flip top application. Latch is located in center horizontal compartment. EACH \$ \_\_\_\_\_
- Option 14K.** Minimum 25” high panel extension cover with minimum 42” locking rear doors which will provide a minimum 48” interior height for storage and work area (Canopy roof style). EACH \$ \_\_\_\_\_
- Option 14L.** Body to have 3 section, tempered steel telescopic sliding roof and two piece, rigid aluminum, endgate cover to protect cargo area from weather and theft. A mechanical type seal will be placed on the telescopic sliding roof and end gate cover EACH \$ \_\_\_\_\_
- Option 14M.** Crane mount reinforced rigidly while maintaining full compartment space on top rear corner of body either left or right for a 3500 lbs. capacity crane (with nomounting holes or bolt holes, we will drill to suit ourselves) EACH \$ \_\_\_\_\_

- Option 14N. Raise Telescopic Roof to get 36" clearance for the above option EACH \$ \_\_\_\_\_
- Option 14O. One - double bottle gas drop well with minimum 55" clearance height (for large bottle use) and retainers EACH \$ \_\_\_\_\_
- Option 14P. Commercial grade spray on bed lining to be applied in the cargo area of the utility body, to include floor, sides tailgate, front, and horizontal surface of bumper EACH \$ \_\_\_\_\_
- Option 14Q. Heavy-duty 5 or 6 speed manual transmission in lieu of automatic transmission EACH \$ \_\_\_\_\_
- Option 14R. Heavy duty, Class V (2-1/2" square tube) receiver trailer hitch. Includes an adapter to reduce to 2" (Class III/IV) and a seven-wire RV style trailer plug EACH \$ \_\_\_\_\_
- Option 14S. Exterior color to be Federal Standard #595B "Highway" EACH \$ \_\_\_\_\_
- Option 14T. Standard gasoline engine with the highest cooling capacity in lieu of diesel engine (state size and horsepower) EACH \$ \_\_\_\_\_
- SIZE \_\_\_\_\_ HORSEPOWER \_\_\_\_\_
- Option 14U. Automatic transmission power take-off provision EACH \$ \_\_\_\_\_
- Option 14V. 2 Full-length cab steps or running boards. (one on drivers side, one on passenger side) SET \$ \_\_\_\_\_
- Option 14W. Four wheel drive GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 14X. Optional Rear Axle Ratio Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 14Y. Limited Slip Rear Axle. Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 14Z. Electric Trailer Brake Controller EACH \$ \_\_\_\_\_
- Option 14AA. Bluetooth Capability EACH \$ \_\_\_\_\_

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

*% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_*

Delivery will be made approximately \_\_\_\_\_ days after receipt of order.

**ITEM # 15 - New standard equipped 2014 or Newer Model 17,500 LB, GVWR Chassis-Cab with DRW and 60" CA**

**ACCEPTABLE MAKES AND MODELS:**

Standard Ford Super Duty F550 with 141" Wheelbase Cab to Axle 60"  
Dodge 5500 with 144.0" Wheelbase, Cab to Axle 60.2"  
International TerraStar with 134" Wheelbase, Cab to Axle 59.6"  
Freightliner M2 106 with 130" Wheelbase, Cab to Axle 61.4"

**All units bid must contain the following options:**

1. Standard diesel Engine with the highest cooling capacity (Size \_\_\_\_\_ Horsepower \_\_\_\_\_)
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic transmission (Speeds \_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(4) manufacturer's standard all season, plus full size spare and wheel (Size \_\_\_\_\_)
7. Rubber flooring
8. Minimum GVWR 17,500 LB
9. Brakes 4-wheel anti-lock braking system (ABS)
10. Speed control and tilt wheel
11. Back up alarm
12. Vinyl seats
13. 3 sets of keys

**DEALER COMPLETE IN DETAIL:**

2014 MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_

FUEL CAPACITY \_\_\_\_\_ FUEL CAPACITY (2) \_\_\_\_\_ OIL CAPACITY \_\_\_\_\_

BUMPER TO BUMPER WARRANTY \_\_\_\_\_

POWERTRAIN WARRANTY \_\_\_\_\_

EXTENDED WARRANTY \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 15**

Indicate the additional cost or deduction for the below listed options. Prices should include all required options and special equipment.

Option 15A.1 Mounted 9' platform body meeting Specification E1320DRW EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 15A.2 Mounted 9' aluminum platform body meeting Specification E1320DRW EACH \$ \_\_\_\_\_  
(Minimum 1 1/4" aluminum extruded floor instead of steel)

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 15B.1 Mounted 9' platform dump body meeting Specification E1327 EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 15B.2 Mounted 9' aluminum platform dump body meeting Specification E1327 EACH \$ \_\_\_\_\_  
(Minimum 1 1/4" aluminum extruded floor instead of steel)

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 15C.1 Mounted 9' dump body meeting Specification E1335 EACH \$ \_\_\_\_\_  
MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 15C.2 Mounted 9' aluminum dump body meeting Specification E1335-ALUM EACH \$ \_\_\_\_\_  
MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 15D Permanently installed bulkhead to fit truck application EACH \$ \_\_\_\_\_  
(minimum requirement to top of cab)

Option 15E. Provide live hydraulics with under hood clutch pump. Pump shall be cast iron EACH \$ \_\_\_\_\_  
design capable of 3500 PSI; aluminum pumps will not be accepted. Reservoir shall  
be 15 gallon with filtered breather cap, suction strainer, sight gauge and in tank  
return filter rated to 25 GPM. Control valve shall be 3 section mobile stack valve  
for hoist, plow and spreader. Valve shall be 12VDC activated capable of a minimum  
12 GPM and installed in a valve enclosure. Control valve must have a main relief  
and a relief for the hoist down function. The hoist, plow and spreader functions  
shall be controlled by a Certified Power Freedom 2.0 12VDC control console with  
automated spreading for mounted dump body in specification E1335 or mounted  
platform body in specification E1327. This package shall be capable of driving the  
auger, spinner motor in a salt spreader, and power to raise angle plow. All hoses  
shall be provided from front to rear of truck.

Option 15F. Hydraulic system to run body, plow and spreader, hoist and plow controls to be EACH \$ \_\_\_\_\_  
manual cable controlled and the spreader control shall be a Certified Power  
Freedom 2.0 automated spreader control. The hydraulic system requirements  
shall match the 15E specifications.

Option 15G. Provide hydraulics and controls 12VDC activated for dump hoist only EACH \$ \_\_\_\_\_

Option 15H. Mounted standard utility tool body. EACH \$ \_\_\_\_\_

Acceptable makes and models are:

Knapheide 6108D54J, Stahl CHALLENGER II 108VVD- 54  
Reading CLASSIC II 108A DW Omaha 108D54V  
RKI L60DW94.

Body to include flush mounted LED tail, stop, turn, backup and clearance  
lights as required per FMVSS 108 standards. Unit must include a  
tread plate step bumper with pintle hook recess.

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 15I. Six - 2" deep full width 250 lbs. capacity free sliding tool drawers EACH \$ \_\_\_\_\_  
mounted approximately 1 1/2" from top of compartment with  
approximately 2 1/2" between trays in lieu of two shelves and dividers  
in one of the full height vertical compartments

Option 15J. Two full length 250 lbs. capacity free sliding tool trays with metal EACH \$ \_\_\_\_\_  
dividers with slots on 4" centers with first tray mounted 5 1/4 "  
from bottom of compartment with approximately 1 1/2" between  
trays with second tray mounted above first in lieu of shelf and  
dividers in one of the horizontal compartments.

Option 15K. Flip top for Utility Body: Top of compartment opens for storage. Can be either EACH \$ \_\_\_\_\_  
side or both sides. Telescopic roof and crane mounting kit will impact flip top  
application. Latch is located in center horizontal compartment.

- Option 15L.** One full- length (or from crane mounting point) 4” deep top opening compartment with release located inside side compartment, automatic up position latch and metal dividers with slots on 4” centers in addition to the standard tool compartments. The top opening compartment will not protrude more than 2” into side compartment (The side compartment shall be 27” from floor to top of side body plus excess for flip top compartment) EACH \$ \_\_\_\_\_
- Option 15M.** One double- bottle gas drop well and retainers in lieu of two shelves and dividers in one of the full height vertical compartments EACH \$ \_\_\_\_\_
- Option 15N.** Minimum 25” high panel extension cover with minimum 42” locking rear doors which will provide a minimum 48” interior height for storage and work area (Canopy roof style). EACH \$ \_\_\_\_\_
- Option 15O.** Body to have 3 section, tempered steel telescopic sliding roof and two piece, rigid aluminum, endgate cover to protect cargo area from weather and theft. A mechanical type seal will be placed on the telescopic sliding roof and end gate cover EACH \$ \_\_\_\_\_
- Option 15P.** Raise Telescopic Roof to get 36” clearance for the above option EACH \$ \_\_\_\_\_
- Option 15Q.** Crane mount reinforced rigidly while maintaining full compartment space on top rear corner of body either left or right for a 3500 lbs. cap. crane (with no mounting holes or bolt holes, we will drill to suit ourselves) EACH \$ \_\_\_\_\_
- Option 15R.** Commercial grade spray on bed lining to be applied in the cargo area of the utility body, to include floor, side’s tailgate, front, and horizontal surface of bumper EACH \$ \_\_\_\_\_
- Option 15S.** Heavy-duty manual 5 or 6 speed transmission in lieu of automatic transmission EACH \$ \_\_\_\_\_
- Option 15T.** Heavy duty, Class V (2-1/2” square tube) receiver trailer hitch. Includes an adapter to reduce to 2” (Class III/IV) and a seven-wire RV style trailer plug EACH \$ \_\_\_\_\_
- Option 15U.** Exterior color to be Federal Standard #595B “Highway Yellow” EACH \$ \_\_\_\_\_
- Option 15V.** Standard gasoline engine with the highest cooling capacity in lieu of diesel engine (state size and horsepower) EACH \$ \_\_\_\_\_
- SIZE \_\_\_\_\_ HORSEPOWER \_\_\_\_\_
- Option 15W.** Automatic transmission power take-off provision EACH \$ \_\_\_\_\_
- Option 15X.** 2 cab steps. (One on driver’s side, one on passenger side) SET \$ \_\_\_\_\_
- Option 15Y.** Optional Rear Axle Ratio Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 15Z.** Limited Slip Rear Axle. Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 15AA.** Electric Trailer Brake Controller EACH \$ \_\_\_\_\_
- Option 15BB.** Bluetooth Capability EACH \$ \_\_\_\_\_

Please indicate below the percent (%) discount off Manufacturer’s Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

*% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_*

**Delivery will be made approximately \_\_\_\_\_ days after receipt of order.**

**ITEM # 16 - New standard equipped 2014 or Newer Model 17,500 GVWR Chassis-Cabs with DRW and 84" CA. ACCEPTABLE MAKES AND MODELS:**

Ford Super Duty F550 with 165" Wheelbase Cab to Axle 84"  
 Dodge 5500 with 168.3" Wheelbase, Cab to Axle 84.2"  
 International TerraStar with 158" Wheelbase, Cab to Axle 83.6"  
 Freightliner M2 106 with 153" Wheelbase, Cab to Axle 84"

**All units bid must contain the following options:**

1. Standard, diesel engine with the highest cooling capacity (Size \_\_\_\_\_ Horsepower \_\_\_\_\_)
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds \_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(4) manufacturer's standard all season, plus full size spare and wheel (Size \_\_\_\_\_)
7. Rubber flooring
8. Minimum GVWR. 17,500 LB
9. Brakes 4-wheel anti-lock braking system (ABS)
10. Speed control and tilt wheel
11. Back up alarm
12. Vinyl seats
13. 3 sets of keys

**DEALER COMPLETE IN DETAIL:**

2014 MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_

FUEL CAPACITY \_\_\_\_\_ FUEL CAPACITY (2) \_\_\_\_\_ OIL CAPACITY \_\_\_\_\_

BUMPER TO BUMPER WARRANTY \_\_\_\_\_

POWERTRAIN WARRANTY \_\_\_\_\_

EXTENDED WARRANTY \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 16**

Indicate the additional cost or deduction for the below listed options. Prices should include all required options and special equipment.

Option 16A.1 Mounted 12' platform body meeting Specification E1320DRW EACH \$ \_\_\_\_\_  
 MAKE \_\_\_\_\_ MODEL) \_\_\_\_\_

Option 16A.2 Mounted 12' aluminum platform body meeting Specification E1320DRW EACH \$ \_\_\_\_\_  
 (Minimum 1 1/4" aluminum extruded floor instead of steel)  
 MAKE \_\_\_\_\_ MODEL) \_\_\_\_\_

Option 16B.1 Mounted 11' platform dump body meeting Specification E1327 EACH \$ \_\_\_\_\_  
 MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

Option 16B.2 Mounted 11' aluminum platform dump body meeting Specification E1327 EACH \$ \_\_\_\_\_  
 (Minimum 1 1/4" aluminum extruded floor instead of steel)  
 MAKE \_\_\_\_\_ MODEL \_\_\_\_\_

- Option 16C.** Permanently installed bulkhead to fit truck application (minimum requirement to top of cab) EACH \$ \_\_\_\_\_
- Option 16D.** Provide live hydraulics with under hood clutch pump. Pump shall be cast iron design capable of 3500 PSI; aluminum pumps will not be accepted. Reservoir shall be 15 gallon with filtered breather cap, suction strainer, sight gauge and in tank return filter rated to 25 GPM. Control valve shall be 3 section mobile stack valve for hoist, plow and spreader. Valve shall be 12VDC activated capable of a minimum 12 GPM and installed in a valve enclosure. Control valve must have a main relief and a relief for the hoist down function. The hoist, plow and spreader functions shall be controlled by a Certified Power Freedom 2.0 12VDC control console with automated spreading for mounted dump body in specification E1335 or mounted platform body in specification E1327. This package shall be capable of driving the auger, spinner motor in a salt spreader, and power to raise angle plow. All hoses shall be provided from front to rear of truck. EACH \$ \_\_\_\_\_
- Option 16E.** Hydraulic system to run body, plow and spreader, hoist and plow controls to be manual cable controlled and the spreader control shall be a Certified Power Freedom 2.0 automated spreader control. The hydraulic system requirements shall match the 16D specifications. EACH \$ \_\_\_\_\_
- Option 16F.** Provide hydraulics and controls 12VDC activated for dump hoist only EACH \$ \_\_\_\_\_
- Option 16G.** Mounted standard utility tool body.
- Acceptable makes and models are:
- |                            |                                |
|----------------------------|--------------------------------|
| Knapheide 6132D54J         | Stahl CHALLENGER II 132 VVD-54 |
| Reading CLASSIC II 132A DW | RKI L84DW94                    |
| Omaha 132D54V              |                                |
- Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess. EACH \$ \_\_\_\_\_
- (MAKE) \_\_\_\_\_ (MODEL) \_\_\_\_\_
- Option 16H.** Six - 2” deep full width 250 lbs. capacity free sliding tool drawers mounted approximately 1 ½” from top of compartment with approximately 2 ½” between trays in lieu of three shelves and dividers in one of the full height vertical compartments EACH \$ \_\_\_\_\_
- Option 16I.** Two full length 250 lbs. capacity free sliding tool trays with metal dividers with slots on 4” centers with first tray mounted 5 ¼ “ from bottom of compartment with approximately 1 ½” between trays with second tray mounted above first in lieu of shelf and dividers in one of the horizontal compartments EACH \$ \_\_\_\_\_
- Option 16J.** Flip top for Utility Body: Top of compartment opens for storage. Can be either side or both sides. Telescopic roof and crane mounting kit will impact flip top application. Latch is located in center horizontal compartment EACH \$ \_\_\_\_\_
- Option 16K.** Minimum 25” high panel extension cover with minimum 42” locking rear doors which will provide a minimum 48” interior height for storage and work area (Canopy roof style). EACH \$ \_\_\_\_\_
- Option 16L.** Body to have 3 section, tempered steel telescopic sliding roof and two piece, rigid aluminum, endgate cover to protect cargo area from weather and theft. A mechanical type seal will be placed on the telescopic sliding roof and end gate cover EACH \$ \_\_\_\_\_

- Option 16M. Raise Telescopic Roof to get 36" clearance for the above option EACH \$ \_\_\_\_\_
- Option 16N. Crane mount reinforced rigidly while maintaining full compartment space on top rear corner of body either left or right for a 3500 lbs. cap. crane (with no mounting holes or bolt holes, we will drill to suit ourselves) EACH \$ \_\_\_\_\_
- Option 16O. One - double bottle gas drop well with minimum 55" clearance height (for large bottle use) and retainers in lieu of the interior 48" full height vertical compartment EACH \$ \_\_\_\_\_
- Option 16P. Heavy-duty manual 5 or 6 speed transmission in lieu of automatic transmission EACH \$ \_\_\_\_\_
- Option 16Q. Heavy duty, Class V (2-1/2 " square tube) receiver trailer hitch. Includes an adapter to reduce to 2" (Class III/IV) and a seven - wire RV style trailer plug EACH \$ \_\_\_\_\_
- Option 16R. Exterior color to be Federal Standard #595B "Highway Yellow" EACH \$ \_\_\_\_\_
- Option 16S. Standard gasoline engine with the highest cooling capacity in lieu of diesel engine (state size and horsepower) EACH \$ \_\_\_\_\_
- SIZE \_\_\_\_\_ HORSEPOWER \_\_\_\_\_
- Option 16T. Automatic transmission power take-off provision EACH \$ \_\_\_\_\_
- Option 16U. 2 Full-length cab steps or running boards. (one on drivers side, one on passenger side) SET \$ \_\_\_\_\_
- Option 16V. 19,000 GVWR Package in lieu of the 17,500 GVWR. (State Wheelbase and Cab to Axle) EACH \$ \_\_\_\_\_
- WHEELBASE \_\_\_\_\_ CA \_\_\_\_\_
- Option 16W. Optional Rear Axle Ratio Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 16X. Limited Slip Rear Axle. Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 16Y. Commercial grade spray on bed lining to be applied in the cargo area of the utility body, to include floor, sides tailgate, front, and horizontal surface of bumper EACH \$ \_\_\_\_\_
- Option 16Z. Electric Trailer Brake Controller EACH \$ \_\_\_\_\_
- Option 16AA. Bluetooth Capability EACH \$ \_\_\_\_\_

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_

Delivery will be made approximately \_\_\_\_\_ days after receipt of order.

**ITEM # 17 - New standard equipped 2014 or Newer 2WD Model Carryalls.**

**ACCEPTABLE MAKES AND MODELS:**

Standard Chevrolet C20906 Suburban with 130.0" Wheelbase  
Standard GMC TC20906 Yukon XL with 130.0" Wheelbase  
Standard Ford Expedition EL with 130.0" Wheelbase

**All units bid must contain the following options:**

1. Standard minimum V8 gasoline engine (Size \_\_\_\_\_ Horsepower \_\_\_\_\_)
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds \_\_\_\_\_)
4. Front and rear heat/air conditioning
5. LH & RH manual mirrors
6. Tires:(4) manufacturer's standard all season, plus full size spare and wheel (Size \_\_\_\_\_)
7. Standard seating with second and third row bench seat
8. Minimum GVWR 7,600 LB
9. Brakes 4-wheel anti-lock braking system (ABS)
10. Speed control and tilt wheel
11. Cloth seats
12. 3 sets of keys

**DEALER COMPLETE IN DETAIL:**

2014 MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ FUEL CAPACITY \_\_\_\_\_ OIL CAPACITY \_\_\_\_\_

IS THIS ENGINE E-85 COMPATIBLE? \_\_\_\_\_ IF SO WHAT IS E-85 MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_

BUMPER TO BUMPER WARRANTY \_\_\_\_\_

POWERTRAIN WARRANTY \_\_\_\_\_

EXTENDED WARRANTY \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item #17**

Indicate the additional cost or deduction for the below listed options. Prices should include all required options and special equipment.

Option 17A. Deep tinted windows EACH \$ \_\_\_\_\_

Option 17B. Heavy-duty, Type V with a Type III adapter trailer hitch. Special equipment which includes weight distributing hitch platform and wiring harness for an 7 pin commercial truck connector. EACH \$ \_\_\_\_\_

Option 17C. Exterior color to be Federal Standard #595B "Highway Yellow" EACH \$ \_\_\_\_\_

Option 17D. Delete 3<sup>rd</sup> row rear bench seat EACH \$ \_\_\_\_\_ (Deduct)

Option 17E. Standard diesel engine in lieu of gasoline engine (State size and horsepower) EACH \$ \_\_\_\_\_  
SIZE \_\_\_\_\_ HORSEPOWER \_\_\_\_\_

Option 17F. 2 Full length cab steps or running boards. (One on Drivers Side, one on Passenger side) SET \$ \_\_\_\_\_

- Option 17G. Optional Rear Axle Ratio Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_**
- Option 17H. Limited Slip Rear Axle Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_**
- Option 17I. Vinyl seats in lieu of cloth seats. EACH \$ \_\_\_\_\_**
- Option 17J. Bluetooth Capability EACH \$ \_\_\_\_\_**

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

*% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_*

**Delivery will be made approximately \_\_\_\_\_ days after receipt of order.**

**ITEM # 18 - New standard equipped 2014 or Newer 4WD Model Carryalls.**

**ACCEPTABLE MAKES AND MODELS:**

Standard Chevrolet C20906 Suburban with 130.0" Wheelbase  
Standard GMC TC20906 Yukon XL with 130.0" Wheelbase  
Standard Ford Expedition EL with 130.0" Wheelbase

**All units bid must contain the following options:**

1. Standard minimum V8 gasoline engine (Size \_\_\_\_\_ Horsepower \_\_\_\_\_)
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds \_\_\_\_\_)
4. Front and rear heat/air conditioning
5. LH & RH manual mirrors
6. Tires:(4) manufacturer's standard all season, plus full size spare and wheel (Size \_\_\_\_\_)
7. Rubber flooring
8. Standard seating with second and third row bench seat
9. Minimum GVWR 7,600 LB
10. Brakes 4-wheel anti-lock braking system (ABS)
11. Speed control and tilt wheel
12. Cloth seats
13. 3 sets of keys

**DEALER COMPLETE IN DETAIL:**

2014 MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ FUEL CAPACITY \_\_\_\_\_ OIL CAPACITY \_\_\_\_\_

IS THIS ENGINE E-85 COMPATIBLE? \_\_\_\_\_ IF SO WHAT IS E-85 MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_

BUMPER TO BUMPER WARRANTY \_\_\_\_\_

POWERTRAIN WARRANTY \_\_\_\_\_

EXTENDED WARRANTY \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 18**

Indicate the additional cost or deduction for the below listed options. Prices should include all required options and special equipment.

Option 18A. Deep tinted windows EACH \$ \_\_\_\_\_

Option 18B. Heavy-duty, Type V with a Type III adapter trailer hitch. Special equipment which includes weight distributing hitch platform and wiring harness for a 7 pin commercial truck connector. EACH \$ \_\_\_\_\_

Option 18C. Exterior color to be Federal Standard #595B "Highway Yellow" EACH \$ \_\_\_\_\_

Option 18D. Delete 3<sup>rd</sup> row rear bench seat EACH \$ \_\_\_\_\_ (Deduct)

Option 18E. Standard diesel engine in lieu of gasoline engine (State size and horsepower) EACH \$ \_\_\_\_\_

SIZE \_\_\_\_\_ HORSEPOWER \_\_\_\_\_

Option 18F. 2 Full length cab steps or running boards. (One on Drivers Side, one on Passenger side) SET \$ \_\_\_\_\_

- Option 18G. Optional Rear Axle Ratio** Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 18H. Limited Slip Rear Axle.** Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 18I. Vinyl seats in lieu of cloth.** EACH \$ \_\_\_\_\_
- Option 18J. Bluetooth Capability** EACH \$ \_\_\_\_\_

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

*% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_*

**Delivery will be made approximately \_\_\_\_\_ days after receipt of order.**

**Item #19 – New standard equipped 2014 or Newer Model 15 Passenger Van**

**ACCEPTABLE MAKES AND MODELS:**

Ford E350 Super Duty Extended E series Wagon, Wheelbase 138” Body code S31  
Chevrolet / GMC Model Extended Wheelbase 155” Model G33706

**All units bid must contain the following options:**

1. Standard minimum V8 gas engine (Size \_\_\_\_\_ Horsepower \_\_\_\_\_)
2. Manufacturer’s standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds \_\_\_\_\_)
4. Factory installed front and rear heat/air conditioning
5. LH & RH manual mirrors
6. Tires:(4) manufacturer’s standard all season, plus full size spare and wheel (Size \_\_\_\_\_)
7. Deep tinted windows (privacy glass)
8. 4 wheel anti-lock braking system (ABS)
9. Minimum GVWR 9100 lb
10. Speed control and tilt wheel
11. Vinyl seats
12. 3 sets of keys

**DEALER COMPLETE IN DETAIL:**

2014 MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ FUEL CAPACITY \_\_\_\_\_ OIL CAPACITY \_\_\_\_\_

IS THIS ENGINE E-85 COMPATIBLE? \_\_\_\_\_ IF SO WHAT IS E-85 MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_

BUMPER TO BUMPER WARRANTY \_\_\_\_\_

POWERTRAIN WARRANTY \_\_\_\_\_

EXTENDED WARRANTY \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 19**

Indicate the additional cost or deduction for the below listed options. Prices should include all required options and special equipment.

- |             |                                                                                                                                                                                             |                     |               |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|---------------|
| Option 19A. | Larger gas engine                                                                                                                                                                           | Size _____ HP _____ | EACH \$ _____ |
| Option 19B. | Power windows and power door locks                                                                                                                                                          |                     | EACH \$ _____ |
| Option 19C. | Towing Package: Manufacturer’s standard to include heavy duty charging, engine oil and transmission cooling, Class III frame hitch and 4 pin wiring installed plus wiring harness for 7 pin |                     | EACH \$ _____ |
| Option 19D. | Sliding side door                                                                                                                                                                           |                     | EACH \$ _____ |
| Option 19E. | Exterior color to be Federal Standard #595B “Highway Yellow”                                                                                                                                |                     | EACH \$ _____ |
| Option 19F. | Bluetooth Capability                                                                                                                                                                        |                     | EACH \$ _____ |

Please indicate below the percent (%) discount off Manufacturer’s Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

*% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_*

Delivery will be made approximately \_\_\_\_\_ days after receipt of order.

## **Body Equipment**

For each Body Company that is included in your bid, please list below the location of service center(s) for the equipment that is to be provided.

Body Company \_\_\_\_\_

Service Location(s) \_\_\_\_\_

# VENDOR INFORMATION & PREFERENCE CERTIFICATION FORM

## Vendor Information

**All bidders must furnish ALL applicable information requested below**

<b>Vendor Name/Mailing Address:</b>  Email Address:	<b>Vendor Contact Information (including area codes):</b> Phone #: Cellular #: Fax #:									
<b>Printed Name of Responsible Officer or Employee:</b>	<b>Signature:</b>									
<b>For Corporations</b> - State in which incorporated:	<b>For Others</b> - State of domicile:									
If the address listed in the Vendor Name/Mailing Address block above is not located in the State of Missouri, list the address of Missouri offices or places of business:  If additional space is required, please attach an additional sheet and identify it as <b><u>Addresses of Missouri Offices or Places of Business.</u></b>										
<b>M/WBE INFORMATION:</b> List all certified Minority or Women Business Enterprises ( <b><u>M/WBE</u></b> ) utilized in the fulfillment of this bid. Include <u>percentages</u> for subcontractors and identify the M/WBE certifying agency: <table style="width: 100%; border: none;"> <thead> <tr> <th style="text-align: center; border: none;"><u>M/WBE Name</u></th> <th style="text-align: center; border: none;"><u>Percentage of Contract</u></th> <th style="text-align: center; border: none;"><u>M/WBE Certifying Agency</u></th> </tr> </thead> <tbody> <tr> <td style="border: none;">_____</td> <td style="border: none;">_____</td> <td style="border: none;">_____</td> </tr> <tr> <td style="border: none;">_____</td> <td style="border: none;">_____</td> <td style="border: none;">_____</td> </tr> </tbody> </table> If additional space is required, please attach an additional sheet and identify it as <b><u>M/WBE Information</u></b>		<u>M/WBE Name</u>	<u>Percentage of Contract</u>	<u>M/WBE Certifying Agency</u>	_____	_____	_____	_____	_____	_____
<u>M/WBE Name</u>	<u>Percentage of Contract</u>	<u>M/WBE Certifying Agency</u>								
_____	_____	_____								
_____	_____	_____								

## Preference Certification

**All bidders must furnish ALL applicable information requested below**

<b><u>GOODS/PRODUCTS MANUFACTURED OR PRODUCED IN USA:</u></b> If any or all of the goods or products offered in the attached bid which the bidder proposes to supply to the MHTC are <b><u>not</u></b> manufactured or produced in the "United States", or imported in accordance with a qualifying treaty, law, agreement, or regulation, list below, by item or item number, the country other than the United States where each good or product is manufactured or produced.	
Item (or item number)	Location Where Item is Manufactured or Produced
If additional space is required, please attach an additional sheet and identify it as <b><u>Location Products are Manufactured or Produced.</u></b>	

**MISSOURI SERVICE-DISABLED VETERAN BUSINESS:** Please complete the following if applicable. Additional information may be requested if preference is applicable. See below definitions for qualification criteria:

**Service-Disabled Veteran** is defined as any individual who is disabled as certified by the appropriate federal agency responsible for the administration of veterans' affairs.

**Service-Disabled Veteran Business** is defined as a business concern:

- a. Not less than fifty-one (51) percent of which is owned by one or more service-disabled veterans or, in the case of any publicly owned business, not less than fifty-one (51) percent of the stock of which is owned by one or more service-disabled veterans; and
- b. The management and daily business operations of which are controlled by one or more service-disabled veterans.

Veteran Information

Business Information

\_\_\_\_\_  
Service-Disabled Veteran's Name (Please Print)

\_\_\_\_\_  
Service-Disabled Veteran Business Name

\_\_\_\_\_  
Service-Disabled Veteran's Signature

\_\_\_\_\_  
Missouri Address of Service Disabled Veteran Business

**NOTICE OF COOPERATIVE PURCHASING**

**MODOT IS INTERESTED IN ASSISTING MISSOURI GOVERNMENTAL ENTITIES, ETC. IN PURCHASING EQUIPMENT, VARIOUS MATERIALS, AND SUPPLIES THAT MEET THE MISSOURI DEPARTMENT OF TRANSPORTATION SPECIFICATIONS.**

Each bidder is asked to indicate below whether they would be willing to offer light duty vehicles listed in the attached "Request for Bid" for sale to these local political entities at the same bid price offered to MoDOT.

It is understood MoDOT will not issue purchase orders, accept delivery nor make payment for these items ordered by any of these agencies. It is further understood the price is based on the light duty vehicle meeting MoDOT specifications. Any added options, deletions, or extra freight costs would be negotiated between the local agency and the successful vendor.

Indicate below whether your company is willing to offer such cooperative purchasing for Missouri counties, cities or other political entities.

YES \_\_\_\_\_ NO \_\_\_\_\_

If the price varies throughout the state on MoDOT bids because of different delivery destinations, please indicate the price F.O.B. your location that would be offered as described.

F.O.B. Location \_\_\_\_\_

Indicate the deadline date that orders will be accepted. \_\_\_\_\_

COMPANY NAME \_\_\_\_\_

ADDRESS \_\_\_\_\_

E-MAIL \_\_\_\_\_

PHONE NUMBER \_\_\_\_\_

SIGNATURE \_\_\_\_\_

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

**ANTI-COLLUSION STATEMENT**

STATE OF \_\_\_\_\_ )

\_\_\_\_\_ )

COUNTY OF \_\_\_\_\_ )

**SS.**

\_\_\_\_\_  
\_\_\_\_\_ being first

duly sworn, deposes and says that he is \_\_\_\_\_  
Title of Person Signing

of \_\_\_\_\_  
\_\_\_\_\_  
Name of Bidder

that all statements made and facts set out in the bid for the above project are true and correct; and that the bidder (The person, firm, association, or corporation making said bid) has not, either directly or indirectly, entered into any agreement, participated in any collusion, or otherwise taken any action in restraint of free competitive bidding in connection with such bid or any contract which may result from its acceptance.

Affiant further certifies that bidder is not financially interested in, or financially affiliated with, any other bidder for the above project.

By \_\_\_\_\_

By \_\_\_\_\_

By \_\_\_\_\_

Sworn to before me this \_\_\_\_\_ day of \_\_\_\_\_, 20\_\_\_\_\_.

\_\_\_\_\_  
Notary Public

My Commission Expires \_\_\_\_\_

**Missouri Highways and Transportation Commission**  
**Standard Bid Provisions, General Terms and Conditions and Special Terms and Conditions**

**STANDARD SOLICITATION PROVISIONS**

- a. The solicitation for the procurement of the supplies referenced therein, to which these "Standard Bid Provisions, General Terms and Conditions and Special Terms and Conditions" are attached, is being issued under, and governed by, the provisions of Title 7 – Missouri Department of Transportation, Division 10 – Missouri Highways and Transportation Commission, Chapter 11 – Procurement of Supplies, of the Code of State Regulations. The Missouri Highways and Transportation Commission (**MHTC**), acting by and through its operating arm, the Missouri Department of Transportation (**MoDOT**), draws the Bidder's attention to said 7 CSR 10-11 for all the provisions governing solicitation and receipt of bids/quotes and the award of the contract pursuant to this solicitation.
- b. All bids/quotes must be signed with the firm name and by a responsible officer or employee. Obligations assumed by such signature must be fulfilled.

**GENERAL TERMS AND CONDITIONS**

**Definitions**

Capitalized terms as well as other terms used but not defined herein shall have the meaning assigned to them in section 7 CSR 10-11.010 Definition of Terms.

**Nondiscrimination**

- a. The Contractor shall comply with all state and federal statutes applicable to the Contractor relating to nondiscrimination, including, but not limited to, Chapter 213, RSMo; Title VI and Title VII of Civil Rights Act of 1964 as amended (42 U.S.C. Sections 2000d and 2000e, *et seq.*); and with any provision of the "Americans with Disabilities Act" (42 U.S.C. Section 12101, *et seq.*)
- b. **Sanctions for Noncompliance:** In the event of the Contractor's noncompliance with the nondiscrimination provisions of this contract, MHTC shall impose such contract sanctions as it or the Federal Highway Administration may determine to be appropriate, including, but not limited to:
  - i. withholding of payments to the Contractor under the contract until the Contractor complies, and/or,
  - ii. cancellation, termination or suspension of the contract, in whole or in part.

**Contract/Purchase Order**

- a. By submitting a bid/quote, the Bidder agrees to furnish any and all equipment, supplies and/or services specified in the solicitation documents, at the prices quoted, pursuant to all requirements and specifications contained therein.
- b. A binding contract shall consist of: (1) the solicitation documents, amendments thereto, and/or Best and Final Offer (BAFO) request(s) with any changes/additions, (2) the Contractor's bid response, and (3) the MHTC's acceptance of the bid by post-award contract or purchase order.
- c. A notice of award does not constitute an authorization for shipment of equipment or supplies or a directive to proceed with services. Before providing equipment, supplies and/or services, the Contractor must receive a properly authorized notice to proceed and/or purchase order.

**Applicable Laws and Regulations**

- a. The contract shall be construed according to the laws of the State of Missouri. The Contractor shall comply with all local, state, and federal laws and regulations related to the performance of the contract. The exclusive venue for any legal proceeding relating to or arising, out of the contract shall be in the Circuit Court of Cole County, Missouri.
- b. The Contractor must be registered and maintain good standing with the Secretary of State of the State of Missouri, Missouri Department of Revenue, and other regulatory agencies, as may be required by law or regulations. Prior to the issuance of a purchase order and/or notice to proceed, the Contractor may be required to submit to MHTC a copy of their current Authority Certificate from the Secretary of State of the State of Missouri and/or a copy of their Certificate of No Tax Due from the Missouri Department of Revenue.
- c. Prior to the issuance of a purchase order and/or notice to proceed, all **out-of-state** Contractors **providing services** within the state of Missouri must submit to MHTC a copy of their current Transient Employer Certificate from the Missouri Department of Revenue, in addition to a copy of their current Authority Certificate from the Secretary of State of the State of Missouri.

**Executive Order:**

The Contractor shall comply with all the provisions of Executive Order 07-13, issued by the Honorable Matt Blunt, Governor of Missouri, on the sixth (6<sup>th</sup>) day of March, 2007. This Executive Order, which promulgates the State of Missouri's position to not tolerate persons who contract with the state engaging in or supporting illegal activities of employing individuals who are not eligible to work in the United States, is incorporated herein by reference and made a part of this Agreement.

- 1) "By signing this Agreement, the Contractor hereby certifies that any employee of the Contractor assigned to perform services under the contract is eligible and authorized to work in the United States in compliance with federal law."
- 2) In the event the Contractor fails to comply with the provisions of the Executive Order 07-13, or in the event the Commission has reasonable cause to believe that the contractor has knowingly employed individuals who are not eligible to work in the United States in violation of federal law, the Commission reserves the right to impose such contract sanctions as it may determine to be appropriate, including but not limited to contract cancellation, termination or suspension in whole or in part or both.
- 3) The Contractor shall include the provisions of this paragraph in every subcontract. The Contractor shall take such action with respect to any subcontract as the Commission may direct as a means of enforcing such provisions, including sanctions for noncompliance.

**Preferences**

- a. In the evaluation of bids/quotes, preferences shall be applied in accordance with 7 CSR 10-11.020(7). Contractors should apply the same preferences in selecting subcontractors. The attached document entitled "**VENDOR INFORMATION AND PREFERENCE CERTIFICATION FORM**" must be completed and returned with the solicitation documents.
- b. Bidders are encouraged to obtain minority business enterprise (MBE) and women business enterprise (WBE) participation in this work through the use of subcontractors, suppliers, joint ventures, or other arrangements that afford meaningful participation for M/WBEs. Bidders are encouraged to obtain 10% MBE and 5% WBE participation.

**Missouri Highways and Transportation Commission**  
**Standard Bid Provisions, General Terms and Conditions and Special Terms and Conditions**

**Cancellation of Contract**

The MHTC may cancel the Contract at any time for a material breach of contractual obligations or for convenience by providing Contractor with written notice of cancellation. Should the MHTC exercise its right to cancel the contract for such reasons, cancellation will become effective upon the date specified in the notice of cancellation sent to the Contractor.

**Bankruptcy or Insolvency**

Upon filing for any bankruptcy or insolvency proceeding by or against the Contractor, whether voluntarily, or upon the appointment of a receiver, trustee, or assignee, for the benefit of creditors, the Commission reserves the right and sole discretion to either cancel the Agreement or affirm the Agreement and hold the Contractor responsible for damages.

**Warranty**

The Contractor expressly warrants that all equipment, supplies, and/or services provided shall: (1) conform to each and every specification, drawing, sample or other description which was furnished to or adopted by the MHTC, (2) be fit and sufficient for the purpose expressed in the solicitation documents, (3) be merchantable, (4) be of good materials and workmanship, and (5) be free from defect.

**Status of Independent Contractor**

The Contractor represents itself to be an independent Contractor offering such services to the general public and shall not represent itself or its employees to be an employee of the MHTC. Therefore, the Contractor shall assume all legal and financial responsibility for taxes, FICA, employee fringe benefits, workers' compensation, employee insurance, minimum wage requirements, overtime, etc., and agrees to indemnify, save and hold the MHTC, its officers, agents and employees harmless from and against any and all losses (including attorney fees) and damage of any kind related to such matters.

**Non-Waiver**

If one of the parties agrees to waive its right to enforce any term of this Contract, that party does not waive its right to enforce such term at any other time or to enforce any or all other terms of this Contract.

**Indemnification**

The Contractor shall defend, indemnify and hold harmless MHTC, including its members and department employees, from any claim or liability whether based on a claim for damages to real or personal property or to a person for any matter relating to or arising out of the Contractor's performance of its obligations under the contract awarded pursuant to this solicitation.

**Missouri Highways and Transportation Commission**  
**Standard Bid/Proposal Provisions, General Terms and Conditions and Special Terms and Conditions**

**SPECIAL TERMS AND CONDITIONS**

**Tax Exempt Status:**

MHTC is exempt from paying Missouri Sales Tax, Missouri Use Tax and Federal Excise Tax. However, the Contractor may themselves be responsible for the payment of taxes on materials they purchase to fulfill the contract. A Project Tax Exemption Certificate will be furnished to the successful Bidder upon request if applicable.

**Liquidated Damages**

- a. In the event the successful Contractor fails to deliver the material within the time specified, the Department and the public will sustain damages because of such delay in delivery, the exact extent of which would be difficult to ascertain, and in order to liquidate such damage in advance it is agreed that the **sum of \$100 per day, per item**, for each assessable calendar day on which the delivery has not been completed, is reasonable and the best estimate which the parties can arrive at as liquidated damages, and it is therefore agreed that said amount will be withheld from payments due the Contractor or otherwise collected from the Contractor as liquidated damages.
- b. **Saturdays, Sundays, holidays and days whereas the Department has suspended work** shall not be assessable days.